



without screw and plug

item code	material	clp. r/r [mm]	ps [pcs]	ref.
SP8Niro	V2A	8	300	063 884
SP8Cu	Cu	8	300	063 850

SP+ID, grip-type conductor holder with ISO plug; stainless steel 8 mm, with self-tapping ISO plug e.g. for insulated exterior plaster



item code	material	clp. r/r [mm]	ps [pcs]	ref.
SP8Niro+ID	V2A/K	8	200	082 229

SD, snap-type conductor holder; screw-less fastening system for conductors



item code	material	L [mm]	colour	ps [pcs]	ref.
SD25grey	Nylon	25	grey	200	063 812
SD25Cu-brown	Cu	25	brown	200	063 811
SD40grey	Nylon	40	grey	150	063 814
SD40Cu-brown	Cu	40	brown	150	063 813

DLH/SP, grip-type roof conductor holder; for tiled, slated and bitumen sheeting roofs

straight version



item code	material	L [mm]	ps [pcs]	ref.
DLH250SPCu	Cu	250	100	063 907
DLH250SPNiro	V2A	250	100	063 908
DLH400SPCu	Cu	400	50	064 516
DLH400SPNiro	V2A	400	50	064 515

straight serrated version



item code	material	L [mm]	ps [pcs]	ref.
DLH190SPCu	Cu	190	100	063 903
DLH190SPNiro	V2A	190	100	063 904
DLH250SP/G/Cu	Cu	250	100	065 665
DLH250SP/G/Niro	V2A	250	100	065 664



angled version

item code	material	L [mm]	ps [pcs]	ref.
DLH140SPCu	Cu	140	150	063 911
DLH140SPAl	Al	140	150	063 910
DLH140SPNiro	V2A	140	150	063 912

DLH/SD, grip-type roof conductor holder; for tiled, slated and bitumen sheeting roofs



straight version

item code	material	L [mm]	ps [pcs]	ref.
DLH250SDCu	Cu	250	100	063 905
DLH250SDNiro	V2A	250	100	063 906



straight serrated version

item code	material	L [mm]	ps [pcs]	ref.
DLH190SD25Cu	Cu	190	100	063 913
DLH190SD25Niro	V2A	190	100	063 914
DLH190SD60Cu	Cu	190	75	063 915
DLH190SD60Niro	V2A	190	75	063 909



angled version

item code	material	L [mm]	ps [pcs]	ref.
DLH140SDCu	Cu	140	150	063 946
DLH140SDAl	Al	140	150	063 945
DLH140SDNiro	V2A	140	150	063 947

DLH/KTSP, roof conductor holder with sleeve; weather-proof sleeve and grip-type conductor holder, drilling hole 10.5 mm, e.g. for masoned ridges



item code	material	clp. r/r [mm]	ps [pcs]	ref.
DLH/KTSPNiro	V2A/K	8	100	083 080
DLH/15KTSPNiro	V2A/K/Al	8	100	083 084