

Insulated Spacers

insulated spacers made of fibreglass reinforced Nylon Ø 25 mm, for maintaining separation distances

IDH25-T/RS 200-600, insulated spacer in trapeze shape for mounting on pipes Ø 200-600 mm; with hinges for vertical adjustments, for installation of interception rods Ø 16 mm on pipes



item code	material	ins. dist. [mm]	pieces	ref.
IDH750-25-T/16Niro/RS 200-600m	NGF/V2A	650	1	084 823
IDH1000-25-T/16Niro/RS 200-600	NGF/V2A	850	1	084 824

IDH25-T/BPL2f, insulated spacer in trapeze shape with 2 mounting brackets; with hinges for vertical adjustments, for installation of interception rods Ø 16 mm on walls



item code	material	ins. dist. [mm]	pieces	ref.
IDH750-25-T/16Niro/BPL2f. Al	NGF/V2A/Al	650	1	084 825
IDH1000-25-T/16Niro/BPL2f. Al	NGF/V2A/Al	850	1	084 826

IDH25-T/WA, insulated spacer in trapeze shape with 90° elbow connection Ø 10 mm for mounting with fold or multi-purpose clamps; for installation of interception rods Ø 16 mm



item code	material	ins. dist. [mm]	pieces	ref.
IDH750-25-T/16Niro/WA rd10Niro	NGF/V2A	650	1	084 827
IDH1000-25-T/16Niro/WA rd10Nir	NGF/V2A	850	1	084 828