

IDH25-T/GB, insulated spacer in trapeze shape with threaded bolts M10x30 mm; bolts slewable by 180°, for installation of interception rods Ø 16 mm



item code	material	ins. dist. [mm]	pieces	ref.
IDH750-25-T/16Niro/GB M10x30GN	NGF/V2A	650	1	084 829
IDH1000-25-T/16Niro/GB M10x30G	NGF/V2A	850	1	084 830

IDH25-T/RS WG, insulated spacer in trapeze shape with pipe clamps, horizontally arranged; slewable, for installation of interception rods Ø 16 mm



item code	material	pipe clp. [inch]	ins. dist. [mm]	pieces	ref.
IDH750-25-T/16Niro/RS 1 1 1/2-2"	NGF/V2A	1 1/2 - 2	650	1	084 831
IDH1000-25-T/16Niro/RS 1 1/2-2"	NGF/V2A	1 1/2 - 2	850	1	084 832
IDH750-25-T/16Niro/RS 2 1/4-3"	NGF/V2A	2 1/4 - 3	650	1	084 833
IDH1000-25-T/16Niro/RS 2 1/4-3"	NGF/V2A	2 1/4 - 3	850	1	084 834

IDH25-T/RS SG, insulated spacer in trapeze shape with pipe clamps, vertically arranged; slewable, for installation of interception rods Ø 16 mm



item code	material	pipe clp. [inch]	ins. dist. [mm]	pieces	ref.
IDH750-25-T/16Niro/RS 1 1/2-2"	NGF/V2A	1 1/2 - 2	650	1	084 835
IDH1000-25-T/16Niro/RS 1 1/2-2"	NGF/V2A	1 1/2 - 2	850	1	084 836
IDH750-25-T/16Niro/RS 2 1/4-3"	NGF/V2A	2 1/4 - 3	650	1	084 837
IDH1000-25-T/16Niro/RS 2 1/4-3"	NGF/V2A	2 1/4 - 3	850	1	084 838