

Fireray 50 RV, with one prism



Part No.: 761315

Approval: VdS

Description

The detector consists of an infrared transmitter and receiver. The signal is reflected by a prism and analysed by the receiving element. Signal reaching the threshold will trigger an alarm.

The actuation on the loop and the resetting function is carried out via the esserbus transponder 808613.10.

Actuation on a conventional line is carried out via the reset module 781332. The device requires a separate voltage supply of 24 V DC.

The Fireray is installed approx. 0.3 to 0.8 m underneath the ceiling and its reflector with the same ceiling distance opposite. There should be no reflecting obstacles in the transmission zone (approx. 2 degrees).

Features

- A compact housing
- Maximum range 5 m to 50 m
- Robust construction
- Complies with EN 54-12 standard
- Actuation and resetting is carried out via the esserbus transponder 808613.10 during loop operation

Technical Data

Operating voltage	10.2 ... 30 V DC
Quiescent current @ 24 V DC	approx. 4 mA
Contact load	max. 30 V DC / 1 A
Alarm display	LED, red
Range	5 to 50 m

Ambient temperature	-20 °C ... 55 °C
Storage temperature	-35 °C ... 60 °C
Type of protection	IP50
Housing	ABS plastic, flame resistant
Air humidity	0% ... 93%, (non-condensing)
Color	gray, similar to RAL 7035
Weight	approx. 670 g
Detector specification	EN 54-12
Abmessungen	W: 210 mm H: 117 mm D: 120 mm

Additional information

Scope of delivery

1 prism 761322

Downloads