

Accessories

761501



Indicator and operating module LRS 110 - Esser, German



Approval: VdS

For displaying the current smoke density and the alarm level of the LRS 100 detector unit and the LRS compact/net. In addition, the alarm and fault status are shown by LEDs. Different functions e.g. *buzzer off* and *reset* can be controlled via the key pad. The unit is also equipped with 7 freely configurable, floating contacts.

Technical Data

Operating voltage	18V DC to 30V DC
Current consumption	110mA to 130mA
Type of protection	IP 30
Ambient temperature	0°C to +39°C
Cable connection	screw terminals for ø 0.2mm - 2.5mm² cable
Weight	1 kg
Housing	metal
Colour	grey, similar to RAL 7035
Dimensions (WxDxH)	140 x 150 x 90mm



As the LRS compact/net recognises up to three alarm states, the LED's for main alarm 1 and main alarm 2 are activated jointly.
For flush mounting, order kit with Part No. 761511 separately.
Programming via Interfaced network.

762401



Indicator and operating module LRS 110 - Esser, English

As 761501, but Esser - English

762411



Indicator and operating module LRS 110 - Esser, French

As 761501, but Esser - French

762421



Indicator and operating module LRS 110 - Esser, Italian

As 761501, but - Esser, Italian

762431



Indicator and operating module LRS 110 - Esser, Spanish

As 761501, but - Esser, Spanish

761507



Indicator and operating module LRS-120 - Esser, German



Approval: VdS

As 761501 but without relays.

762402



Indicator and operating module LRS-120 - Esser, English

As 761507 but Esser - English