

Standard LED remote indicator panel - ESSER



Part No.: 764790

Approval: VdS

Description

Additional indicator for up to 32 alarm, trouble or collective signals. Connection via an integrated 32-pin terminal strip. The indicator is controlled via relay contacts or semiconductor outputs with positive-guided contacts in the hazard detection system. With key for lamp testing, integrated buzzer and easy-to-maintain terminal card. Elegant plastic housing for surface mounting.

Technical Data

| | |
|------------------------------------|---|
| Operating voltage | 10 ... 15 V DC |
| Quiescent current @ 12 V DC | approx. 1 mA |
| Alarm current @ 12 V DC | approx. 380 mA (incl. 32 LED & buzzer) |
| Display | 32 LED, red |
| Ambient temperature | -5 °C ... 50 °C |
| Storage temperature | -25 °C ... 75 °C |
| Type of protection | IP 40 |
| Housing | ABS plastic |
| Air humidity | ≤ 95% (w/o condensation) |
| Color | white (similar to RAL 9003), front blue (similar to RAL 5003) |
| Weight | approx. 1000 g |
| Abmessungen | W: 270 mm H: 221 mm D: 71 mm |

Additional information

This indicator panel is not suitable for application as an initial warning device for the fire brigade.

Downloads