


SPRINT ATEX EMC cable glands LowTemp, metric, earthing cones to DIN 89345, stainless steel 1.4404

SPRINT ATEX EMV-Kabelverschraubungen LowTemp, metrisch, Erdungseinsatz DIN 89345, Edelstahl 1.4404



Explosion protection: II 2 G Ex e II
II 2 D Ex tD A21 IP68

Certificates: PTB 05 ATEX 1098 X

Protection class to EN 60 529: IP 68 to 5 bar (30 min)

Protection class to DIN 40 050-T9: IP 69K

Temperature range: -60°C to 75°C

Material: - Cable gland: Stainless steel A4 (1.4404) (X2CrNiMo 17 12 2 / AISI 316L)

- Clamping cage: polyamide

- Gasket: silicone

Equipment: - EMC gland with inserts according to DIN 89345

- Continuous EMC protection due to earthing cones

- Maximum traction relief through WISKA patent lamella

- Seal-tight to enclosure rack through additional silicone O-ring

- Same sealing range and on all SPRINT-glands

- available with dust protection gasket

Explosionsschutz: II 2 G Ex e II
II 2 D Ex tD A21 IP68

Bescheinigungen: PTB 05 ATEX 1098 X

Schutzart gemäß EN 60 529: IP 68 to 5 bar (30 min)

Schutzart gemäß DIN 40 050-T9: IP 69K

Einsatztemperatur: -60°C bis 75°C

Material: - Verschraubung: Edelstahl A4 (1.4404) (X2CrNiMo 17 12 2 / AISI 316L)

- Klemmkäfig: Polyamid

- Dichtung: Silikon

Ausstattung: - EMV-Verschraubung mit Innenteilen nach DIN 89345

- Dauerhafte Kontaktierung des Schirmgeflechts durch Erdungskonen

- Optimale Abdichtung Zugentlastung durch patentiertes WISKA-

Lamellensystem

- Abdichtung am Gehäuse durch zusätzlichen Silikon O-Ring

- Gleiche Dichtbereiche und Schlüsselweiten für alle SPRINT-

Verschraubungen

- Lieferung mit Staubschutzscheibe

Type	WISKA-No.						TL	
			mm	mm	mm	mm	mm	
ESSKE-4 12 LT EMV-Z	10065358	10	M 12x1,5	5	4 · 7	5	17	23 · 30
ESSKE-4 16 LT EMV-Z	10065359	10	M 16x1,5	5	5 · 10	6	22	26 · 34
ESSKE-4 20 LT EMV-Z	10065360	10	M 20x1,5	6	6 · 13	7	24	29 · 37
ESSKE-4 25 LT EMV-Z	10065361	10	M 25x1,5	7	10 · 17	14	30	33 · 42
ESSKE-4 32 LT EMV-Z	10065362	5	M 32x1,5	8	13 · 21	18	36	36 · 44
ESSKE-4 40 LT EMV-Z	10065363	5	M 40x1,5	8	16 · 28	24	46	44 · 55
ESSKE-4 50 LT EMV-Z	10065364	2	M 50x1,5	9	21 · 35	30	55	51 · 62
ESSKE-4 63 LT EMV-Z	10065365	1	M 63x1,5	10	34 · 48	39	68	56 · 67