


Cable glands, PG, circular, Typ W, thread to DIN 40430

Kabelverschraubungen, PG, Typ W, Gewinde nach DIN 40430



Protection class to EN 60 529: IP 54; installation with connection thread gasket IP 66

Temperature range: -40°C to 100°C, interm. up to approx. 120°C

Material: - Cable gland: brass (nickel-plated or chromium-plated on request)

- Gasket: EPDM

Equipment: Cable gland according to DIN 89280 for non-armoured cable

Schutzart gemäß EN 60 529: IP 54; bei Montage mit Anschlussgewindedichtring IP 66

Einsatztemperatur: -40°C bis 100°C, kurzzeitig bis 120°C

Material: - Verschraubung: Messing blank (vernickelt oder verchromt auf Anfrage)

- Dichtung: EPDM

Ausstattung: Kabeleinführung nach DIN 89280 aus Messing für Kabel ohne Schirmung

Type	WISKA-No. bright / blank						TL
			mm	mm	mm	mm	mm
KVMP 18/9-W8	10011025	1	PG 9	8	7 · 8,5	19	41
KVMP 18/9-W10	10011026	1	PG 9	8	8 · 10,5	19	41
KVMP 24/9-W12	10011035	1	PG 9	9	10 · 12,5	24	47
KVMP 18/11-W8	10011027	1	PG 11	8	7 · 8,5	19	41
KVMP 18/11-W10	10011028	1	PG 11	8	8 · 10,5	19	41
KVMP 24/11-W12	10011041	1	PG 11	9	10 · 12,5	24	47
KVMP 24/11-W14	10011042	1	PG 11	9	12 · 14,5	24	47
KVMP 18/13,5-W8	10011029	1	PG 13,5	8	7 · 8,5	19	41
KVMP 18/13,5-W10	10011030	1	PG 13,5	8	8 · 10,5	19	41
KVMP 24/13,5-W12	10011047	1	PG 13,5	9	10 · 12,5	24	47
KVMP 24/13,5-W14	10011048	1	PG 13,5	9	12 · 14,5	24	47
KVMP 18/16-W8	10011031	1	PG 16	8	7 · 8,5	19	41
KVMP 18/16-W10	10011032	1	PG 16	8	8 · 10,5	19	41
KVMP 24/16-W12	10011053	1	PG 16	9	10 · 12,5	24	47
KVMP 24/16-W14	10011054	1	PG 16	9	12 · 14,5	24	47
KVMP 24/16-W16	10011055	1	PG 16	9	14 · 16,5	24	47
KVMP 24/16-W17	10011056	1	PG 16	9	16 · 17,5	24	47
KVMP 24/21-W12	10011059	1	PG 21	9	10 · 12,5	24	47
KVMP 24/21-W14	10011060	1	PG 21	9	12 · 14,5	24	47
KVMP 24/21-W16	10011061	1	PG 21	9	14 · 16,5	24	47
KVMP 24/21-W17	10011062	1	PG 21	9	16 · 17,5	24	47

Cable glands, PG, circular, Typ W, thread to DIN 40430

Kabelverschraubungen, PG, Typ W, Gewinde nach DIN 40430

Type	WISKA-No. bright / blank						TL
			mm	mm	mm	mm	mm
KVMP 30/21-W18	10011079	1	PG 21	10	16 · 18,5	30	51
KVMP 30/21-W20	10011080	1	PG 21	10	18 · 20,5	30	51
KVMP 30/29-W18	10011082	1	PG 29	10	16 · 18,5	30	51
KVMP 30/29-W20	10011083	1	PG 29	10	18 · 20,5	30	51
KVMP 36/29-W22	10011099	1	PG 29	11	20 · 22,5	36	56
KVMP 36/29-W24	10011100	1	PG 29	11	22 · 24,5	36	56
KVMP 36/29-W26	10011101	1	PG 29	11	24 · 26,5	36	56
KVMP 36/36-W22	10011104	1	PG 36	11	20 · 22,5	36	56
KVMP 36/36-W24	10011105	1	PG 36	11	22 · 24,5	36	56
KVMP 36/36-W26	10011106	1	PG 36	11	24 · 26,5	36	56
KVMP 45/36-W28	10011118	1	PG 36	11	26 · 28,5	46	59
KVMP 45/36-W30	10011119	1	PG 36	11	28 · 30,5	46	59
KVMP 45/36-W32	10011120	1	PG 36	11	30 · 32,5	46	59
KVMP 45/42-W30	10011122	1	PG 42	11	28 · 30,5	46	59
KVMP 45/42-W32	10011123	1	PG 42	11	30 · 32,5	46	59
KVMP 56/42-W35	10011130	1	PG 42	12	32 · 35,5	55	65
KVMP 56/42-W38	10011131	1	PG 42	12	35 · 38,5	55	65
KVMP 56/42-W41	10011132	1	PG 42	12	38 · 41,5	55	65
KVMP 56/48-W38	10011134	1	PG 48	12	35 · 38,5	55	65
KVMP 56/48-W41	10011135	1	PG 48	12	38 · 41,5	55	65
KVMP 72/48-W44	10011140	1	PG 48	12	41 · 44,5	70	69
KVMP 72/48-W48	10011141	1	PG 48	12	44 · 48,5	70	69
KVMP 72/48-W52	10011142	1	PG 48	12	48 · 52,5	70	69

KUNSTSTOFF
PLASTIC

MEMBRAN
MEMBRANE

MESSING
BRASS

DIN 89280

EDELSTAHL
STAINL. STEEL

EMV
EMC

ATEX

VerGland

BS 6121

DICHTUNGEN
SEALINGS

WERKZEUGE
TOOLS

TECHNIK
TECHNICS

INDEX
INDEX