


SPRINT ATEX cable glands, NPT

SPRINT ATEX Kabelverschraubungen, NPT



Explosion protection: II 2 G Ex e II

II 2 D Ex tD A21 IP68

Certificates: PTB 04 ATEX 1112 X

Protection class to EN 60 529: IP 68 to 5 bar (30 min)

Protection class to DIN 40 050-T9: IP 69K

Temperature range: -40°C to 75°C

Material: - Cable gland: brass nickel-plated

- Clamping cage: polyamide

- Gasket: EPDM

Equipment: - Maximum traction relief through WISKA patent lamella

- Seal-tight to enclosure rack through additional EPDM sealing ring

- Same sealing range and key width on all SPRINT-glands

- Also available with reduction insert, multiple sealing insert, special sealing insert

- Incl. dust-protection gasket

Explosionsschutz: II 2 G Ex e II

II 2 D Ex tD A21 IP68

Bescheinigungen: PTB 04 ATEX 1112 X

Schutzart gemäß EN 60 529: IP 68 bis 5 bar (30 min)

Schutzart gemäß DIN 40 050-T9: IP 69K

Einsatztemperatur: -40°C bis 75°C

Material: - Verschraubung: Messing vernickelt

- Klemmkäfig: Polyamid

- Dichtung: EPDM

Ausstattung: - Optimale Abdichtung und Zugentlastung durch patentiertes WISKA-Lamellensystem

- Abdichtung am Gehäuse durch zusätzlichen EPDM O-Ring

- Gleiche Dichtbereiche und Schlüsselweiten für alle SPRINT-Verschraubungen

- Lieferbar mit Reduzierdichteinsatz, Mehrfach- und Sonderdichtungen

- Lieferung mit Staubschutzscheibe

Type	WISKA-No. Ni						TL
			mm	mm	mm	mm	mm
NMSKE 1/4	10101082	50	NPT 1/4"	13	4 · 7	16	33 · 40
NMSKE 3/8	10101083	50	NPT 3/8"	13	5 · 10	20	35 · 42
NMSKE 1/2	10101084	50	NPT 1/2"	16	6 · 13	24	38 · 45
NMSKE 3/4	10101085	50	NPT 3/4"	16	10 · 17	29	40 · 48
NMSKE 1	10101086	25	NPT 1"	20	13 · 21	36	46 · 53
NMSKE 1 1/4	10101087	10	NPT 1 1/4"	20	16 · 28	46	50 · 58
NMSKE 1 1/2	10101088	10	NPT 1 1/2"	20	21 · 35	55	51 · 62
NMSKE 2	10101089	10	NPT 2"	21	34 · 48	68	56 · 67

Recommended accessories:

Empfohlenes Zubehör:



NMMU

Page / Seite 65