


Reduction cable glands, metric, circular, type W

Reduzier-Kabelverschraubungen, metrisch, rund, Typ W



Protection class to EN 60 529: IP 54; installation with connection thread gasket IP 66
Temperature range: -40°C to 100°C, interm. up to approx. 120°C
Material: - Cable gland: brass (nickel-plated or chromium-plated on request)
 - Gasket: EPDM
Equipment: - Reduction cable gland acc. to DIN 89280 for non-armoured cable
 - * Similar to DIN 89280

Schutzart gemäß EN 60 529: IP 54; bei Montage mit Anschlussgewindedichtring IP 66
Einsatztemperatur: -40°C bis 100°C, kurzzeitig bis 120°C
Material: - Verschraubung: Messing blank (vernickelt oder verchromt auf Anfrage)
 - Dichtung: EPDM
Ausstattung: - Reduzier-Kabeleinführung nach DIN 89280 für Kabel ohne Schirmung
 - * Ähnlich DIN 89280

Type	WISKA No. bright / blank						TL
				mm	mm	mm	mm
RVM 24/18-W8	10011259	1		M 24x1,5	11	7,0 · 8,5	44
RVM 24/18-W10	10011260	1		M 24x1,5	11	8,0 · 10,5	44
RVM 30/18-W8	10011261	1		M 30x2	12	7,0 · 8,5	45
RVM 30/18-W10	10011262	1		M 30x2	12	8,0 · 10,5	45
RVM 30/24-W8A	10011263	1		M 30x2	12	7,0 · 8,5	50
RVM 30/24-W10A	10011264	1		M 30x2	12	8,0 · 10,5	50
RVM 30/24-W12	10011265	1		M 30x2	12	10,0 · 12,5	50
RVM 30/24-W14	10011266	1		M 30x2	12	12,0 · 14,5	50
RVM 30/24-W16	10011267	1		M 30x2	12	14,0 · 16,5	50
RVM 30/24-W17	10011268	1		M 30x2	12	16,0 · 17,5	50
RVM 36/24-W8A	10011269	1		M 36x2	13	7,0 · 8,5	51
RVM 36/24-W10A	10011270	1		M 36x2	13	8,0 · 10,5	51
RVM 36/24-W12	10011271	1		M 36x2	13	10,0 · 12,5	51
RVM 36/24-W14	10011272	1		M 36x2	13	12,0 · 14,5	51
RVM 36/24-W16	10011273	1		M 36x2	13	14,0 · 16,5	51
RVM 36/24-W17	10011274	1		M 36x2	13	16,0 · 17,5	51
RVM 36/30-W15	10011275	1		M 36x2	13	14,0 · 15,5	53
RVM 36/30-W18	10011276	1		M 36x2	13	16,0 · 18,5	53
RVM 36/30-W20	10011277	1		M 36x2	13	18,0 · 20,5	53
RVM 45/30-W15	10011278	1		M 45x2	14	14,0 · 15,5	54
RVM 45/30-W18	10011279	1		M 45x2	14	16,0 · 18,5	54
RVM 45/30-W20	10011280	1		M 45x2	14	18,0 · 20,5	54

Reduction cable glands, metric, circular, type W

Reduzier-Kabelverschraubungen, metrisch, rund, Typ W

Type	WISKA-No. bright / blank						TL
			mm	mm	mm	mm	mm
RVM 45/36-W18	10011281	1	M 45x2	14	16,0 · 18,5	36	59
RVM 45/36-W20	10011282	1	M 45x2	14	18,0 · 20,5	36	59
RVM 45/36-W22	10011283	1	M 45x2	14	20,0 · 22,5	36	59
RVM 45/36-W24	10011284	1	M 45x2	14	22,0 · 24,5	36	59
RVM 45/36-W26	10011285	1	M 45x2	14	24,0 · 26,5	36	59
RVM 56/36-W18	10011286	1	M 56x2	15	16,0 · 18,5	36	60
RVM 56/36-W20	10011287	1	M 56x2	15	18,0 · 20,5	36	60
RVM 56/36-W22	10011288	1	M 56x2	15	20,0 · 22,5	36	60
RVM 56/36-W24	10011289	1	M 56x2	15	22,0 · 24,5	36	60
RVM 56/36-W26	10011290	1	M 56x2	15	24,0 · 26,5	36	60
RVM 72/56-W35	10011294	1	M 72x2	16	32,0 · 35,5	55	69
RVM 72/56-W38	10011295	1	M 72x2	16	35,0 · 38,5	55	69
RVM 72/56-W41	10011296	1	M 72x2	16	38,0 · 41,5	55	69
RVM 56/45-W28	50011291	1	M 56x2	15	26,0 · 28,5	36	60
RVM 56/45-W30	50011292	1	M 56x2	15	28,0 · 30,5	36	60
RVM 56/45-W32	50011293	1	M 56x2	15	30,0 · 32,5	36	60