



**Product:** [H124A00](#)

COAX H124 AL PVC CATV

## Product Description

COAX [1.0/4.4] H124 AL PVC CATV

## Technical Specifications

### Product Overview

Environmental Space:	Indoor/Outdoor
Suitable Applications:	Coaxial cables used in cabled distribution networks designed according the European Standard EN 50117; Operating at frequencies between 5 MHz and 2150 MHz; The International Standard IEC 1196

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
18	Solid	BC - Bare Copper	1 mm	0.03 mm	1

Conductor Count: 1

#### Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	FPE - Foamed Polyethylene	4.4 mm	0.15 mm

#### Outer Shield Material

Type	Layer	Material	Coverage [%]	Min. Overlap	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Tape	1	Aluminum/Polyester/Aluminum		2 mm			
Braid	2	TC - Tinned Copper	31 %		5.1 mm	0.2 mm	4 %

#### Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
PVC - Polyvinyl Chloride	5.9 mm	0.2 mm

OuterJacket1, Table Note: According to European Standard HD 624

### Construction and Dimensions

Min Elongation at Breakof Jacket:	150 %
Min Tensile Strength of Jacket:	12.5 MPa

### Electrical Characteristics

#### Conductor DCR

Max. Conductor DCR	Max. Conductor Loop	Max. Shield DCR
23 Ohm/km	58 Ohm/1000ft	35 Ohm/km

#### Capacitance

Nom. Capacitance	Capacitance Tolerance
53 pF/m	2 pF/m

#### Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance

75 Ohm	3 Ohm	Min. 40 dB
--------	-------	------------

#### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
5 MHz	2 dB/100m
50 MHz	4.5 dB/100m
100 MHz	6.4 dB/100m
200 MHz	9.2 dB/100m
400 MHz	13.3 dB/100m
600 MHz	16.5 dB/100m
800 MHz	19.3 dB/100m
1000 MHz	21.8 dB/100m
1350 MHz	25.7 dB/100m
1750 MHz	29.7 dB/100m
2150 MHz	33.4 dB/100m
2400 MHz	35.6 dB/100m

#### Delay

Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
84 %	2 %

#### High Freq

Frequency [MHz]	Min. RL (Return Loss) [dB]
5 - 30 MHz	23 dB
30 - 470 MHz	23 dB
470 - 862 MHz	20 dB
862 - 2400 MHz	18 dB

High Freq Table Note: In each frequency band, 3 peak values up to 4 dB lower are allowed

#### Screening

Frequency [MHz]	Min. Screening Attenuation
30 - 1000 MHz	75 dB

#### Voltage

Voltage Test Dielectric
2.0 kV DC

#### Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-15°C To +70°C
Operating Temp Range:	-15°C To +70°C

#### Mechanical Characteristics

Bulk Cable Weight:	32 kg/km
Max Recommended Pulling Tension:	55 N
Min Bend Radius (W/o Pulling Strength):	30 mm
Crush Resistance:	Max. 1% (load of 700N) N
Adhesion Dielectric:	7.8-78 N at 25 mm N

#### Standards

ISO/IEC Compliance:	IEC 1196
CENELEC Compliance:	EN 50117 and EN 50117-1
RG Type:	6/U Type

#### Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	1998-01-01
---------------------------------------	------------

#### Part Number

#### Variants

Item #	Color	Length
--------	-------	--------

H124A00.00500	White	500 m
H124A00.005000	White	5,000 m
H124A00.00B100	White	100 m
H124A00.00U250	White	250 m
H124A00.015000	White	5,000 m

## History

Update and Revision:	Revision Number: 0.156 Revision Date: 01-31-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.