Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



AX100073 Connectivity Accessories - Right Entry Bracket for Fiber Express Rack Mount 2U



For more Information please call

1-800-Belden1

General Description:

Right Entry Bracket for Fiber Express Rack Mount, 2U, Black

Usage (Overall)

Suitable Applications: Fiber Express Rack Mount 2U FX24RM **Related Parts:** Fiber Express Patch Panel 2U FX24RM in rack or cabinet

Physical Characteristics (Connectivity)

Dimensions

Dimensions:

Height (mm)	Width (mm)	Depth (mm)
74.676	345.948	138.938

Color

Color: Black

Weight

2.223 kg Weight:

Packaging

Packaging: Inividual unit packaged in a carton.

Mechanical Characteristics (Connectivity)

-40°C To +70°C Storage Temperature Range: -10°C To +60°C Installation Temperature Range:

Applicable Specifications and Agency Compliance (Overall)

Suitability

Suitability - Indoor: Yes - Indoor

Notes (Overall)

Notes: Items included: Bracket, Screws 10-32 X .25 LG, Installation Guide PX100104.

Product Family

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX100073	1 EA	4.899 LB			RIGHT SIDE CABLE ENTRYBR

Revision Number: 0 Revision Date: 03-11-2014

© 2016 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Page 1 of 1