# **Detailed Specifications & Technical Data**



## METRIC MEASUREMENT VERSION

## AX100540 Faceplates and Panels - FiberExpress Wall Mount Patch Panel - Medium Wall Mount

			For more Information please call 1-800-Belden1
General Description: FiberExpress Patch Panel, Medi	um Wall Moi	unt Black	
Usage (Overall) Suitable Applications:		FiberExpress Solutions, Backbone, Telecommunications Ro	om. Main Distribution Room
Related Parts:		FiberExpress Adapter Strips, Fiber Splice Organizer Trays a	
Physical Characteristics (Connectivity	)		
Physical Characteristics (Connectivity Capacity	)		
Max. Capacity:		4 Strips; 48 Fibers (SC, SCD, ST, FC); 96 Fibers (LCD, MT- Two 12-inch splice tray kit (A0318904)	RJ). Two 8-inch splice tray kit (A0649869),
Access			
Front Connection:		Flush	
Dimensions Dimensions:			
Height (mm) Width (mm) Depth (mm)   396.494 424.180 139.700			
Materials Materials: Description Material Panel Steel LH Door Steel RH Door Lexan Color			
Color:		Black	
Weight			
Weight:		5.248 kg	
Included Parts Included Parts:		6 Wood Screws (#10x1inch); 2 Velcro Strap; 9 Tie Wrap; 1 / Manual	Admin Label; 1 Caution Label, 1 Installation
Packaging Packaging:		Individually packaged in a cardboard box.	
Mechanical Characteristics (Connectiv	rity)		
Storage Temperature Range:		-40°C To +70°C	
Operating Temperature Range:		-10°C To +60°C	
Applicable Specifications and Agency Suitability	Compliance (	Overall)	
Suitability - Indoor:		Yes	
Notes (Overall)			
. ,	n Guide PX101059 i	ncluded with the product or visit our web site at http://www.belde	n.com
Product Family		· · ·	
Part Numbers: Description It FiberExpress Wall Mount PP, Small, Black A	em Number X100495		
	X100540 X100542		

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX100540	1 EA	0.000 KG			FX MEDIUM WALL-MOUNT PANEL BK



#### METRIC MEASUREMENT VERSION

#### AX100540 Faceplates and Panels - FiberExpress Wall Mount Patch Panel - Medium Wall Mount

Revision Date: 05-28-2009 Revision Number: 0

© 2017 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.