


Security Composite Cables

CCTV Plus Audio or Pan and Tilt CCTV Control Applications



De- scription	Part No.	UL NEC / C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Shielding Material	Nominal OD		Component	Description	Shielding Material & Nom. DCR	Insulation Material & Colors	Component Jacket Material & Colors	Component OD	
			ft.	m	lbs.	kg		inch	mm						inch	mm
Composite • (1) Pair Unshielded 18 AWG • (1) Coax Solid 0.8 mm Bare Copper • 95 % Bare Copper Braid																
PVC Insulation (Pairs) • Foam Insulation (Coax) • Black PVC Jacket																
300V 75°C	549945	NEC: CM CEC: CM FT1	500 1000	152 305	30.0 60.2	13.6 27.3	Unshielded	0.460	11.68	2xData	1-Pair 18 AWG 1.22 mm (7x26) BC	Unshielded	PVC 1.47 mm	PVC Black	0.228	5.79
										1xCoax	20 AWG 0.8 mm Solid BC	95 % BC	Foam Polyolefin	PVC Black	0.232	5.89
RG-59																
Color Code 1-Pair: Black and Red																
PVC Insulation (Pairs) • Foam Insulation (Coax) • Grey FRNC/LSNH Jacket																
300V 70°C	449945	IEC 60754-2	328 1640	100 500	19.8 98.8	9.0 44.8	Unshielded	0.461	11.70	2xData	1-Pair 18 AWG 1.22 mm (7x26) BC	Unshielded	PE 1.47 mm	FRNC Grey	0.228	5.79
										1xCoax	20 AWG 0.8 mm Solid BC	95 % BC	Foam PE	FRNC Grey	0.232	5.90
RG-59																
Color Code 1-Pair: Black and Red																
Composite • (1) Pair Unshielded 18 AWG • (1) Coax Solid 1.0 mm Bare Copper • 95 % Bare Copper Braid																
PVC Insulation (Pairs) • Foam Insulation (Coax) • Black PVC Jacket																
300V 75°C	539945	NEC: CM CEC: CM FT1	500 1000	152 305	34.2 69.0	15.5 31.3	Unshielded	0.500	12.70	2xData	1-Pair 18 AWG 1.22 mm (7x26) BC	Unshielded	PVC 1.47 mm	PVC Black	0.228	5.79
										1xCoax	18 AWG 1.0 mm Solid BC	95 % BC	Foam Polyolefin	PVC Black	0.266	6.76
RG-6 Kötter approved																
Color Code 1-Pair: Black and Red																
PVC Insulation (Pairs) • Foam Insulation (Coax) • Grey FRNC/LSNH Jacket																
300V 70°C	439945	IEC 60754-2	328 1640	100 500	22.9 114.9	10.4 52.1	Unshielded	0.500	12.70	2xData	1-Pair 18 AWG 1.22 mm (7x26) BC	Unshielded	PE 1.47 mm	FRNC Grey	0.228	5.79
										1xCoax	18 AWG 1.0 mm Solid BC	95 % BC	Foam PE	FRNC Grey	0.268	6.80
RG-6 Kötter approved																
Color Code 1-Pair: Black and Red																

BC = Bare Copper • DCR = DC resistance