

Security and Alarm Cables

Commercial Applications Unshielded




De- scription	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

22 AWG • Stranded (7x30) 0.8 mm Bare Copper • Numbered and Color Coded • Rip Cord

PVC Insulation • Grey PVC Jacket

300V
75°C
NEC:
CMR
CEC:
CMF FT4
0.76 mm
22 AWG
(7x30) BC
0.040 1.01 Unshielded see chart below



Rip Cord

5500UE	2 CDR	C-500	C-152	4.0	1.8	0.128	3.25
		U-500	U-152	5.5	2.5		
		500	152	5.5	2.5		
		C-1000	C-305	7.9	3.6		
		U-1000	U-305	9.9	4.5		
1000	305	9.0	4.1				
5501UE	3 CDR	U-1000	U-305	13.0	5.9	0.135	3.43
		1000	305	13.0	5.9		
5502UE	4 CDR	C-500	C-152	7.5	3.4	0.148	3.76
		U-500	U-152	9.0	4.1		
		U-1000	U-305	16.1	7.3		
		1000	305	16.1	7.3		
Also available in White.							
5503UE	5 CDR	U-1000	U-305	20.1	9.1	0.162	4.11
		1000	305	20.1	9.1		
5504UE	6 CDR	C-500	C-152	12.6	5.7	0.177	4.50
		U-500	U-152	14.1	6.4		
		500	152	13.4	6.1		
		U-1000	U-305	27.1	12.3		
		1000	305	27.1	12.3		
Also available in White.							
5506UE	8 CDR	U-1000	U-305	29.1	13.2	0.192	4.88
		1000	305	30.0	13.6		
5508UE	10 CDR	U-1000	U-152	35.9	16.3	0.226	5.74
		1000	305	41.0	18.6		
5509UE	12 CDR	U-500	U-152	21.6	9.8	0.233	5.92
		U-1000	U-305	42.1	19.1		
		1000	305	47.2	21.4		

BC = Bare Copper • DCR = DC resistance

Color Code

Cond. No.	Color	Cond. No.	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Grey
5	Brown	11	Pink
6	Blue	12	Tan