

Security and Alarm Cable

Commercial Applications
Shielded, Plenum-Rated



Shielded Multi-conductor (cont'd.)
CMP FT6 Rated or CL2P Rated

Product Description

Bare copper conductors, Flamarrest® insulation, conductors cabled, overall Beldfoil® tape shield (foil side out) and drain wire, Natural Flamarrest jacket with rip cord. Sequential footage marking every two feet.

Color Code: See chart below.


Specifications

Conductor	Bare Copper
Insulation	Flamarrest
Insulation Thickness	
18 and 16 AWG	.009" (.229mm)
14 and 12 AWG	.011" (.279mm)
Shield	Beldfoil
Jacket	Flamarrest
Approvals	
NEC (18 and 16 AWG)	CMP
CEC (18 and 16 AWG)	CMP FT6
NEC (14 and 12 AWG)	CL2P
NEC Articles	
18 and 16 AWG	800
14 and 12 AWG	725
Voltage Rating	
18 and 16 AWG	300V
14 and 12 AWG	150V
Temperature Rating	75°C

Applications

- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls

Solid Conductor



Shorting Fold

Stranded Conductor



Shorting Fold

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Shielded Multi-conductor (NEC CMP and CEC CMP FT6)

18 AWG										
6320FE	2	solid	C-500 1000	C-152 305	10.5 22.0	4.8 10.0	.015	.38	.150	3.89
6300FE	2	7	C-500 U-500 500 U-1000 1000	C-152 U-152 152 U-305 305	11.0 12.0 12.0 23.0 23.0	5.0 5.4 5.4 10.4 10.4	.015	.38	.162	4.11
6301FE	3	7	U-500 U-1000 1000	U-152 U-305 305	15.5 30.0 31.0	7.0 13.6 14.1	.015	.38	.172	4.37
6302FE	4	7	C-250 U-500 500 U-1000 1000	C-76 U-152 152 U-305 305	8.8 19.5 19.0 37.0 37.0	4.0 8.9 8.6 16.8 16.8	.015	.38	.188	4.78
6304FE	6	7	C-250 U-500 1000	C-76 U-152 305	12.0 25.5 52.0	5.4 11.6 23.6	.015	.38	.226	5.74
6306FE	8	7	1000	305	66.0	30.0	.015	.38	.246	6.25
6307FE	9	7	500 1000	152 305	39.5 73.0	18.0 33.2	.015	.38	.266	6.76
6309FE	12	7	500 1000	152 305	50.5 99.0	22.9 45.0	.018	.46	.306	7.77
16 AWG										
6200FE	2	19	500 1000	152 305	16.5 33.0	7.5 15.0	.015	.38	.184	4.67
6201FE	3	19	500 U-1000 1000	152 U-305 305	22.5 43.0 45.0	10.2 19.5 20.5	.015	.38	.195	4.95
6202FE	4	19	500 1000	152 305	29.0 59.0	13.2 26.8	.015	.38	.215	5.46

Shielded Multi-conductor (NEC CL2P)

14 AWG										
6100FE	2	19	500 U-1000 1000	152 U-305 305	25.0 49.0 51.0	11.3 22.2 23.1	.015	.38	.220	5.59
6101FE	3	19	1000	305	66.0	29.9	.015	.38	.234	5.94
12 AWG										
6000FE	2	19	500 1000	152 305	36.0 68.0	16.4 30.9	.015	.38	.260	6.60

Color Code Chart (18 to 16 AWG)

Cond. No.	Color	Cond. No.	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

(14 to 12 AWG)

Cond. No.	Color
1	Black
2	White
3	Red