

Part Number: 70006PU

# DataTuff® PROFINET Cat 5e Type A - Permanent Installation Cable



# **Product Description**

DataTuff PROFINET Type A, Cat 5e, 100Mb/s, Quad, AWG 22(1), Solid, Foil+ 85% Braid, No Halogen PUR Jacket, UL AWG 20549

# **Technical Specifications**

# **Physical Characteristics (Overall)**

# Conductor Nominal Diameter No. of Conductors 22 Solid BC - Bare Copper 0.65 mm Conductor Count: Total Number of Pairs: 2 Insulation Material Nominal Diameter Diameter +/- Tolerance Polyethylene 1.5 mm Bonded-Pair: No Color Chart Number Quad 1 White & Blue & Yellow & Orange Inner Jacket Material Material Nominal Diameter PVC Bedding 3.9 mm Outer Shield Material Material Thickness of Foil Min. Coverage [%] Tape Aluminum/Polyester 50 μm Braid TC - Tinned Copper 85 % Outer Jacket Material Nominal Diameter Diameter +/- Tolerance PUR (UV stabilised and oil resistant) 6.5 mm 0.2 mm

# **Electrical Characteristics**

# Conductor DCR

Max. Conductor DCR 57.1 Ohm/km

## Impedance

| Frequency [MHz] | Nominal Characteristic Impedance | Nominal Characteristic Tolerance |
|-----------------|----------------------------------|----------------------------------|
| 1 - 100         | 100 Ohm                          | 15 Ohm                           |

#### Delay

Max. Delay Nominal Velocity of Propagation (VP) [%]

#### High Freq

| Frequency<br>[MHz]    | Max. Insertion Loss (Attenuation) | Min. NEXT [dB | Min. ACRF (ELFEXT) [dB]                          | Min. SRL (Structural Return Loss) |
|-----------------------|-----------------------------------|---------------|--|-----------------------------------|
| 1 MHz                 | 2.1 dB/100m                       | 65.3 dB       | 64 dB  |                                   |
| 4 MHz                 | 4.1 dB/100m                       | 56.3 dB       | 52 dB  | 23 dB                             |
| 10 MHz                | 6.5 dB/100m                       | 50.3 dB       | 44 dB  | 25 dB                             |
| 16 MHz                | 8.3 dB/100m                       | 47.2 dB       | 40 dB  | 25 dB                             |
| 31.25 MHz             | 11.7 dB/100m                      | 42.9 dB       | 34 dB  | 23.6 dB                           |
| 62.5 MHz              | 17 dB/100m                        | 38.4 dB       | 28 dB  | 21.5 dB                           |
| 100 MHz               | 22 dB/100m                        | 35.3 dB       | 24 dB  | 20.1 dB                           |
| High Freq Table Note: |                                   |               | Reference standard: ISO/IEC 11801 ed 2.0, Cat 5e |                                   |

Reference standard: ISO/IEC 11801 ed 2.0, Cat 5e

#### Transfer Impedance

| Frequency [MHz] | Transfer Impedance |
|-----------------|--------------------|
| 10 Mhz          | Max. 10 mOhm/m     |

General Electrical Parameters Notes:

#### Voltage

Voltage Rating [V]

### **Temperature Range**

| Installation Temp Range: | -5°C To +50°C  |
|--------------------------|----------------|
| Storage Temp Range:      | -40°C To +80°C |
| Operating Temp Range:    | -40°C To +80°C |

### **Mechanical Characteristics**

| Oil R | esistance: | IEC 60811-2-1 |  |
|-------|------------|---------------|--|

#### **Standards**

| ISO/IEC Compliance: | ISO/IEC 11801 Ed. 2.2:2002/A2:2010/C1:2011 |
|---------------------|--|
| Data Category:      | Category 5e                                |

### **Applicable Environmental and Other Programs**

| Environmental Space:                  | Indoor     |
|---------------------------------------|------------|
| EU RoHS Compliance Date (yyyy-mm-dd): | 2015-11-11 |

# Flammability, LS0H, Toxicity Testing

| ISO/IEC Flammability: | IEC 60332-1-2 |
|-----------------------|---------------|

### **Part Number**

#### Variants

| Item #        | Color | Length |
|---------------|-------|--------|
| 70006PU.01305 | Green | 305 m  |
| 70006PU.01500 | Green | 500 m  |
| Patent:       |       |        |

# History

| Update and Revision: | Revision Number: 0.168 Revision Date: 09-17-2019 |
|----------------------|--|
|                      |  |

# © 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.