

Plenum-Rated

Individually Shielded Pairs

Audio, Control and Instrumentation Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

22 AWG Stranded (7x30) TC Conductors • Twisted Pairs • Individually Shielded Beldfoil® (100% Coverage) • 22 AWG Stranded TC Drain Wire††


Plenum • FEP Insulation • Natural Flamarrest® Jacket

300V RMS 	82723	NEC:	2	Red & Black, Green & White	U-500	U-152.4	10.5	4.8	14.7Ω/M'	16.6Ω/M'	.153	3.89	36	62%	43	141	75	246
		CMP			U-1000	U-304.8	20.0	9.1	48.2Ω/km	54.5Ω/km								
		CEC:			1000	304.8	19.0	8.6										
		CMP FT6			U-2000	U-609.6	40.0	18.2										

Z-Fold®

††82723 has 24 AWG drain wire

Pairs cabled on common axis to reduce diameter.

300V RMS 	82777	NEC:	3	See Chart 3 (Tech Info Section)	U-500	U-152.4	19.5	8.9	14.7Ω/M'	11.3Ω/M'	.237	6.02	46	62%	35	115	76	249
		CMP			U-1000	U-304.8	38.0	17.3	48.2Ω/km	37.1Ω/km								
		CEC:			1000	304.8	39.0	17.7										
		CMP FT6																

Z-Fold®

82778	NEC:	6	See Chart 3 (Tech Info Section)	1000	304.8	71.0	32.2	14.7Ω/M'	11.3Ω/M'	.314	7.98	46	62%	35	115	76	249
	CMP							48.2Ω/km	37.1Ω/km								
	CEC:																
	CMP FT6																

Plenum • FEP Insulation • Red FEP Jacket

300V RMS 	88723	NEC:	2	Red & Black, Green & White	100	30.5	3.4	1.5	14.7Ω/M'	16.6Ω/M'	.148	3.76	40	69%	35	115	67	220
		CMP			500	152.4	11.0	5.0	48.2Ω/km	54.5Ω/km								
		CEC:			1000	304.8	19.0	8.6										
		CMP FT6																

Z-Fold®

††88723 has 24 AWG drain wire

300V RMS 	88777	NEC:	3	See Chart 3 (Tech Info Section)	100	30.5	6.0	2.7	14.7Ω/M'	11.3Ω/M'	.234	5.94	50	69%	31	102	67	220
		CMP			500	152.4	19.0	8.6	48.2Ω/km	37.1Ω/km								
		CEC:			1000	304.8	42.0	19.1										
		CMP FT6																

Z-Fold®

88778	NEC:	6	See Chart 3 (Tech Info Section)	100	30.5	7.0	3.2	14.7Ω/M'	11.3Ω/M'	.309	7.85	50	69%	31	102	67	220
	CMP			500	152.4	38.5	17.5	48.2Ω/km	37.1Ω/km								
	CEC:			1000	304.8	75.0	34.1										
	CMP FT6																


Pairs cabled on common axis to reduce diameter.

Plenum • FEP Insulation • Red Fluorocopolymer Jacket

300V RMS 	87723	NEC:	2	Red & Black, Green & White	500	152.4	11.0	5.0	14.7Ω/M'	15.0Ω/M'	.148	3.76	40	69%	35	115	67	220
		CMP			1000	304.8	18.0	8.2	48.2Ω/km	49.2Ω/km								
		CEC:																
		CMP FT6																

Z-Fold®

††87723 has 24 AWG drain wire.

300V RMS 	87777	NEC:	3	See Chart 3 (Tech Info Section)	500	152.4	18.0	8.2	14.7Ω/M'	11.3Ω/M'	.234	5.94	50	69%	31	102	67	220
		CMP			1000	304.8	40.0	18.2	48.2Ω/km	37.1Ω/km								
		CEC:																
		CMP FT6																

Z-Fold®

87778	NEC:	6	See Chart 3 (Tech Info Section)	500	152.4	37.5	17.0	14.7Ω/M'	11.3Ω/M'	.309	7.85	50	69%	31	102	67	220
	CMP			1000	304.8	73.0	33.2	48.2Ω/km	37.1Ω/km								
	CEC:																
	CMP FT6																

Pairs cabled on common axis to reduce diameter.

DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.