

Overall Beldfoil® Shield

Audio, Control and Instrumentation Cables
Non-Plenum

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

22 AWG Stranded (7x30) TC Conductors • Conductors Cabled • Overall Beldfoil Shield (100% Coverage) • 22 AWG Stranded TC Drain Wire

Polypropylene Insulation • Brown PVC Jacket

300V RMS	9770	NEC: CM	3	Black, Red,	U-500	U-152.4	9.0	4.1	.008	.20	.020	.51	.145	3.68	32	105	60	197
		CEC: CM		White	500	152.4	9.0	4.1										
					U-1000	U-304.8	18.0	8.2										
					1000	304.8	17.0	7.7										



Z-Fold®

Polyethylene Insulation • Chrome PVC Jacket

UL AWM Style 2093 (300V 60°C)	8771	NEC: CM	3	Black, Red,	250	76.2	6.3	2.8	.016	.41	.033	.84	.199	5.05	23	75	41	134
		CEC: CM		Clear	500	152.4	12.0	5.5										
					U-500	U-152.4	12.0	5.5										
					U-1000	U-304.8	23.0	10.4										
					1000	304.8	24.0	10.9										
					10000†	3048.0	240.0	109.1										




Shorting Fold

22 AWG Stranded (19x34) TC Conductors • Conductors Cabled • Overall Beldfoil Shield (100% Coverage) • 23 and 25 AWG Drain Wires††

Polyethylene Insulation • White PVC Jacket

UL AWM Style 2094 (300V 75°C)	8729	NEC: CM, CL3	4	Black, Red,	U-500	U-152.4	23.0	10.5	.016	.41	.051	1.30	.257	6.53	22	72	42	138
		CEC: CM		Green, Clear	500	152.4	21.5	9.8										
					U-1000	U-304.8	45.0	20.4										
					1000	304.8	47.0	21.4										



Z-Fold®

†† 8729 has three 23 AWG solid and one 25 AWG stranded tinned copper-coated steel drain wires.

20 AWG Stranded (7x28) TC Conductors • Conductors Cabled • Overall Beldfoil Shield (100% Coverage) • 20 AWG Stranded TC Drain Wire

Polyethylene Insulation • Chrome PVC Jacket

UL AWM Style 2093 (300V 60°C)	8772	NEC: CM	3	Black, Red,	U-500	U-152.4	16.0	7.3	.016	.41	.033	.84	.218	5.54	27	89	51	167
		CEC: CM		Clear	500	152.4	16.0	7.3										
					U-1000	U-304.8	31.0	14.1										
					1000	304.8	32.0	14.5										



Z-Fold®

TC = Tinned Copper

*Capacitance between conductors.

**Nominal capacitance conductor to conductor and shield.

†Final put-up may vary -10% to +20%. May contain two pieces, minimum length of any one piece is 1500 ft.