



Identification sign

## **PRODUCT INFORMATION**

## APPLICATION

Used to form a bulkhead for cable wall and ceiling penetration against the effects of fire for a period of 90 minutes in accordance with DIN 4102-9 (fire resistance class S90).

Article No.	Bulkhead	Application	Info
1300 470	Fire protection plug	For provision of a round	Packaging comprises 20 pieces
	BDS	S90 bulkhead in ceilings and	For bore holes up to 65 mm
		walls in accordance with DIN 4102-9	Dry and dust-free assembly,
		problem free installation	
1300 471	Fire protection plug	For provision of a round	Packaging comprises 20 pieces
	BDS	S90 bulkhead in ceilings and	For bore holes up to 78 mm
		walls in accordance with DIN 4102-9	Dry and dust-free assembly,
		problem free installation	
1300 472	Fire protection plug	For provision of a round	Packaging comprises 20 pieces
	BDS	S90 bulkhead in ceilings and	For bore holes up to 108 mm
		walls in accordance with DIN 4102-9	dry and dust-free assembly,
		problem free installation	
1300 473	Fire protection plug	For provision of a round	Packaging comprises 20 pieces
	BDS	S90 bulkhead in ceilings and	For bore holes up to 123 mm
		walls in accordance with DIN 4102-9	Dry and dust-free assembly,
		problem free installation	
1300 474	Fire protection plug	For provision of a round	Packaging comprises 20 pieces
	BDS	S90 bulkhead in ceilings and	For bore holes up to 135 mm
		walls in accordance with DIN 4102-9	Dry and dust-free assembly,
		problem free installation	
1300 475	Fire protection plug	For provision of a round	Packaging comprises 20 pieces
	BDS	S90 bulkhead in ceilings and	For bore holes up to 165 mm
		walls in accordance with DIN 4102-9	Dry and dust-free assembly,
		problem free installation	
1300 476	Fire protection plug	For provision of a round	Packaging comprises 20 pieces
	BDS	S90 bulkhead in ceilings and	For bore holes up to 200 mm
		walls in accordance with DIN 4102-9	Dry and dust-free assembly,
		problem free installation	
1300 477	Fire protection block	For closing gaps	Set consists of 12 cartridges
	BDS-N (1K)	and spandrels and	at 310 ml each, white
		wall soffits	
1300 478	Identification sign	For permanent identification	Set consists of 10
	Fire protection plug	of a cable bulkhead	Identification signs
	Fire protection brick	in accordance with DIN 4102-9	



