

# ENSTO

**PRODUCT SPECIFICATION**

2017-06-16



6418677682896

**NBL210TX15080S****Cable set**

---

|        |                                   |
|--------|-----------------------------------|
| Code   | NBL210TX15080S                    |
| GTIN   | 6418677682896                     |
| Name   | Cable set EnstoNet<br>Blue, 8,0 m |
| Vendor | Ensto Finland Oy<br>CEC           |

**Technical specification**

---

**Dimensions**

|                          |                         |
|--------------------------|-------------------------|
| Weight:                  | 891.8 g                 |
| Conductor cross-section: | 2 x 1,5 mm <sup>2</sup> |
| Cable length:            | 8.0 m                   |
| Length:                  | 8.0 m                   |

**Temperatures**

|                                |                                      |
|--------------------------------|--------------------------------------|
| Max. operating temperature:    | +70 °C                               |
| Min. installation temperature: | +5 °C                                |
| Min. operating temperature:    | -30 °C ( without mechanical stress ) |

**Colors**

|        |      |
|--------|------|
| Color: | Blue |
|--------|------|

**Features**

|                                  |    |
|----------------------------------|----|
| Cable type:                      | HF |
| Description male/female coupler: |    |

**Basic**

Code:

**Ratings**

|                       |           |
|-----------------------|-----------|
| Rated voltage:        | ≥ 250 V   |
| Degree of protection: | IP20      |
| Flammability rating:  | UL 94 V-2 |
| ETIM class:           | EC002587  |

## ETIM

---

### ETIM

|                                   |         |
|-----------------------------------|---------|
| <b>Degree of protection (IP):</b> | IP20    |
| <b>Nominal rated current:</b>     | 16 A    |
| <b>Number of poles:</b>           | 2       |
| <b>Nominal rated voltage:</b>     | 250 V   |
| <b>Total length:</b>              | 8000 mm |
| <b>Mechanical coding:</b>         | 1       |

### Packaging

---

#### Default package

|                      |          |
|----------------------|----------|
| <b>Unit:</b>         | PCS      |
| <b>Size:</b>         | 10       |
| <b>Length:</b>       | 385 mm   |
| <b>Width:</b>        | 260 mm   |
| <b>Height:</b>       | 130 mm   |
| <b>Weight (brt):</b> | 9.168 kg |
| <b>Volume:</b>       | 13.013   |

#### Pallet package

|                      |         |
|----------------------|---------|
| <b>Unit:</b>         | PCS     |
| <b>Size:</b>         | 630     |
| <b>Length:</b>       | 1200 mm |
| <b>Width:</b>        | 800 mm  |
| <b>Height:</b>       | 1060 mm |
| <b>Weight (brt):</b> | 603 kg  |