

ENSTO

NCL330CL08060G

Cable set

| | |
|-------------|---|
| Code | NCL330CL08060G |
| GTIN | 6418677719301 |
| ENumber | |
| Name | Cable set - Grey, 6,0 m |
| Description | |
| Vendor | Ensto Finland Oy  |

Technical specification

Dimensions

| | |
|---------------------------------|---------------------|
| Weight: | 210 g |
| Conductor cross-section: | 0,8 mm ² |
| Cable length: | 6.0 m |

Temperatures

| | |
|---------------------------------------|--------------------------------------|
| Max. operating temperature: | +70 °C |
| Min. installation temperature: | +5 °C |
| Min. operating temperature: | -30 °C (without mechanical stress) |

Colors

| | |
|---------------|------|
| Color: | Grey |
|---------------|------|

Features

| | |
|---|--|
| Cable type: | |
| Description male/female coupler: | |

Basic

| | |
|--------------|--|
| Code: | |
|--------------|--|

Ratings

| | |
|------------------------------|----------|
| Rated voltage: | ≥ 250 V |
| Degree of protection: | IP20 |
| Flammability rating: | |
| ETIM class: | EC002587 |

ETIM

ETIM

| | |
|-----------------------------------|---------|
| Degree of protection (IP): | IP20 |
| Nominal rated current: | 6 A |
| Number of poles: | 3 |
| Nominal rated voltage: | 250 V |
| Total length: | 6000 mm |
| Mechanical coding: | true |

Packaging

Default package

| | |
|----------------------|----------|
| Unit: | PCS |
| Size: | 10 |
| Length: | 405 mm |
| Width: | 300 mm |
| Height: | 245 mm |
| Weight (brt): | 2.447 kg |
| Volume: | 29.768 |

Pallet package

| | |
|----------------------|---------|
| Size: | 320 |
| Length: | 1200 mm |
| Width: | 800 mm |
| Height: | 1130 mm |
| Weight (brt): | 84 kg |
| Volume: | 1084.8 |

