

CSB06 - Compact Termination Box

V.3.1

Description

The compact termination box is designed for use in residential and business applications for the termination of up to four fibres. The wall box enables the installation of either a single Sirocco Blown Tube cable using up to a 4 fibre blown unit or two 2 fibre ruggedised cables to be spliced to four SC pigtails (PC or APC), which connect to adaptors at the base of the unit. The unit can be quickly installed within an office, house or communication room environment.

Features/Benefits

- ▶ Ability to allow cables to enter from rear or bottom of the unit
- ▶ All fibres are positively managed to maintain a 30mm minimum bend radius
- ▶ Tamperproof cover, security screws available as an option
- ▶ Unit manufactured from fire resistant UL94-V0 rated material
- ▶ Patchcords exit unit on bottom face and are protected by two protective covers
- ▶ Ergonomic design
- ▶ Optional removable rear entry cable management
- ▶ Flip tray to allow access to pigtails and cable entry
- ▶ Removable cover for easy access
- ▶ Standard colour white. Other colours available on request



Technical Specification

Compact Termination Box		
Number of splice trays		1
Maximum fibre capacity		4 Fibres
Maximum cable diameter (mm)		10
Maximum no. of customer feeds		4 Patchcords
Required space envelope (mm)		(l) 80 x (w) 120 x (d) 25
Operating temperature		-20°C to + 50°C (5 to 95% RH)
Material	Cap	FR High Impact Polystyrene
	Base	FR High Impact Polystyrene
	Splitter trays	FR High Impact Polystyrene
Packing dimensions		(w) 100 x (h) 150 x (d) 50 mm
Packed weight		0.16 kg
Net weight		0.1 kg
Testing	Optical	Tested 1310nm,1550nm and 1625nm
	Dry heat	BS EN 60068-2-2 Test Bb
	Damp heat	IEC 60068-2-3: 1969
	Change of temperature	IEC 60068-2-14: 1984
	Vibration	IEC 60068-2-6: 1995
	Shock	IEC 60068-2-27: 1987

Ordering Information

Description	Part Number
Compact termination box	CSB06



+44 (0) 870 127 3330



+44 (0) 870 127 3331



sales@fibrefab.com



www.fibrefab.com