

P99 1U Splicing Panel

V.3.1



Features FibreFab's Unique
Speedway Cassette and Spool

Description

FibreFab offers an innovative, robust 1U sliding splicing panel. This panel has been designed to accept up to 48 fibres over 2 x splice cassettes within a 1U space. The new Optronics Speedway splice tray allows splicing of up to 24 fibres per tray using secondary buffered fibres without the need to strip back whilst still accommodating sufficient over length for up to 2 re-splices.

The use of the Optronics Speedway spool ensures the protection of fibre bend radii at all times, with the sliding function providing easy access during installation or re-work.

Features/Benefits

- Suitable for up to 4 incoming cables
- Splicing for up to 48 fibres
- Splicing and fibre bend radius managed by Optronics Speedway Splice Tray and Spool
- ROHS, REACH SvHC
- Fits standard 19"

Applications

- Data centres, premises installations, telecommunication networks
- Ethernet, Fibre Channel, ATM, LAN, MAN and WAN
- Data communication and telecommunication networks
- Indoor applications

Included

- 2 x Strain Tie
- 2 x SPT01 - Speedway Cassettes
- 4 x Spool6 - Speedway Spools
- 2 x Gland



+44 (0) 870 127 3330



+44 (0) 870 127 3331



sales@fibrefab.com



www.fibrefab.com

P99 1U Splicing Panel

Technical Specification

PRODUCT SPECIFICATION	
Height	1U (44.4mm)
Width	482mm
Depth	205mm
Net weight	2.5kg
Packaged weight	3kg
Packaged dimensions	530mm (W) x 250mm (L) x 50mm (H)
Gland Entry Points	2 x 20mm, 2 x 25mm
IP rating	IP20
Number of fibres	48
Mounting Adjustment range	50mm
Material	Cold-rolled steel
Material thickness	1.2mm
Material coating	Powder coating
Colour	RAL 9004
Operating temperature	-40°C to +50°C
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754, EN297-1
Compliant to	RoHS, Reach/SVHC

Ordering Information

DESCRIPTION	PART NO.
1U Splicing Panel	P99XXX00

