

ENSTO

Cabinet wall installation PC

UPCT080604HSF



Code	UPCT080604HSF
GTIN	6438100212209
Name	Cabinet wall installation PC Ensto PolyBox Size 8.0 x 6.0 x 4.0 in, Polycarbonate Wall mount Enclosure, Hinged 2-Screws, Clear Cover, Mounting Flange
Description	Ensto PolyBox is a product family specifically designed for the US market. Robust and tightly sealed, our new JIC sized enclosures are made from top quality polycarbonate. A wide range of configurations can be customized with multiple features.
Vendor	Ensto Building Systems Finland Oy

Technical specification

Certificates

Standards: UL 508A

Dimensions

Volume : 0.00628 cm³
 Inner depth: 105 mm
 Length: 134 mm
 Size: 223 x 210 x 134 mm
 Width: 210 mm
 Height: 223 mm
 Weight: 1.163 kg

Material

Material: Polycarbonate
 Gasket: Polyurethane

Mechanical

Impact strength: IK10 +40C° / -35C°

Ratings

Rated voltage:	1000 ... 1500 V
Flammability rating:	UL 746C 5 inch flame test
Degree of protection:	IP69

Temperatures

Operating temperature:	-40 ... 80 °C
Short term temperature range:	-40 ... 120 °C

US specific

Environmental type:	4X, 12, 13, 6P
Width inch:	8.28 in
Depth inch:	5.27 in
Height inch:	8.78 in
Operating temperature °F:	-40 ... 176 °F
Short term temperature range °F:	-40 ... 248 °F
Weight pound:	2.56 lb
Inner depth inch:	4.13 in
Size inch:	8.78 x 8.28 x 5.27 in

Others

ETIM Class:	EC000261
-------------	----------

ETIM Technical specification

etim

Height:	223 mm
Depth:	134 mm
Material:	Plastic
Material quality:	Other
Surface finishing:	Untreated
Colour:	Grey
RAL-number:	7035
With mounting plate:	No
Mounting plate depth-adjustable:	Yes
Wall build in:	No
Pole fastening:	Yes
Number of doors:	1
Suitable for metrical mounting:	No
Suitable for outdoor set-up:	Yes
Pitched roof:	No
EMC-version:	No
With glazed door:	Yes
With ventilation door:	No
With backside door:	No
Impact strength:	IK10

Degree of protection (NEMA): 6P

Packaging

Default package

Unit:	PCE
Package size:	1
Depth:	229 mm
Width:	229 mm
Height:	148 mm
Weight:	1.286 kg
Volume:	7.761268 l