

Data sheet

ID	SER 50 WH
Description	stop end
Properties	for Starline-trunking SLS
Colour	white, similar to RAL 9010
Fire Behaviour	non flame propagating



UV-Level

L2

Art. no.	Width x Depth	Suitable for	Small Package	Large Package
036 060	170 x 50 mm	Left	10 pc	150 pc
036 061	170 x 50 mm	Right	10 pc	150 pc
086 014	250 x 50 mm	Left	5 pc	80 pc
086 015	250 x 50 mm	Right	5 pc	80 pc

Further technical details

Details

Model	Symmetric
Joint cover	False
Type of fastening	Snap on
Halogen free	False
Surface protection	Untreated
Protection film	False
Material	PVC-U

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.