

Data sheet

ID	SLC
Description	Starline trunking
Properties	compression resistance > 1250 N Properties: for the supply of power, data and telecommunication cabling, versatile system in three standard trunking assemblies, all with three fully segregated compartments, further segregation of services possible by using trunking dividers, special clip-on system for robust connections between trunking body and lid (shock- and child-proof).
Colour	white, similar to RAL 9010
Fire Behaviour	non flame propagating



Norms: EN 50085, BS 4678 Part 4



Length	Number of covers	Number of partitions	UV-Level
3000 mm	1	4	L2

Art. no.	Width x Depth	Small Package	Large Package
082 756	170 x 50 mm	3 m	150 m

Further technical details

Details

Covers supplied with the product True

Symmetric True

Construction type rectangular False

Halogen free False

Surface protection Untreated

Construction rear wall (inner side) Continuous C-profile

Protection film False

With duct connector False

Mounting perforation in base False

Mounting method covers Spanned

With cable fixing clip False

Material PVC-U

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.