

# Data sheet

ID	<b>BR BK</b>
Description	plain ducting
Properties	rigid ducting, plain, with moulded-on coupler medium resistance against compression
Colour	black, similar to RAL 9005
Fire Behaviour	non flame propagating
Classification	N 250



Norms: ÖVE/ÖNORM EN 61386-1:2009, ÖVE/ÖNORM EN 61386-24:2011



Operating temperature	UV-Level
-5 bis +60 °C	L2

Art. no.	Length	Inner diameter	Outer diameter	Small Package	Large Package
106 249 (002339)	6 m	105,6 mm	110 mm	6 m	570 m
106 250 (019030)	6 m	153,6 mm	160 mm	6 m	234 m

## Further technical details

Details	
Model	Rigid
Shape	Outer - and inner side plain
Surface protection	Untreated
Transparent	False
Material	PVC-U

\*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, [www.dietzel-univolt.com](http://www.dietzel-univolt.com), makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.