

Data sheet

ID	KSB 30
Description	slip type bend, with moulded-on coupler
Properties	for sandtight connections of KSR, BR and UDR ductings in an angle of 30°
Colour	black, similar to RAL 9005
Classification	N 450



Norms: ÖVE/ÖNORM EN 61386-1:2009, ÖVE/ÖNORM EN 61386-24:2011



Angle of bow	Operating temperature	UV-Level
30 °	-5 bis +60 °C	L2

Art. no.	Inner diameter	Outer diameter	Small Package	Large Package
001 820	50 mm	54,3 mm	65 pc	-
001 821	63 mm	68 mm	30 pc	-
001 822	75 mm	80,6 mm	15 pc	-
001 823	90 mm	96,5 mm	12 pc	-
001 824	110 mm	117 mm	-	-
001 825	125 mm	133,1 mm	-	-
001 827	160 mm	170 mm	-	-

Further technical details

Details	
Surface protection	Untreated
Surface polished	False
Model	Rigid
Shape	Outer - and inner side plain
Material	PVC-U

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.