

Data sheet

ID	KSBF
Description	pliable ducting bend
Properties	with plain pipe ends, rainwater proof
Colour	white, similar to RAL 9010 black, similar to RAL 9005



Material quality			UV-Level	
Polyethylene (PE)			L3	
Art. no.	Colour	Inner diameter	Outer diameter	Max bending radius
001 902	White	80 mm	90 mm	180 °
001 903	White	100 mm	110 mm	180 °
001 908	White	150 mm	160 mm	180 °
103 609	Black	190 mm	200 mm	180 °

Further technical details

Details

Model	Pliable
-------	---------

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.