

AP Wall outlet IP44

surface / duct mounted

for 2 modules, with key lock



Surface mounted (AP) version

Description

Structured premises cablings in the industrial sector, for the transmission of Ethernet protocols. Wall outlet IP44, surface mounted, for 2 modules. Lockable outlet with protection rating IP44. Cover can also be locked with connected patch cords. One-key system. Cable entry from the top (one or two cables). Shatter-proof, stable housing, grey, similar to RAL 7035. Delivery without modules.

Application

Suitable for the following Datwyler modules:

- PS-GG45 7A shielded
 - RJ45 module MS-K 1/8 Cat. 6/EA shielded
 - RJ45 module MS-K Plus 1/8 Cat. 6A shielded
 - RJ45 module MS-C6A 1/8 Cat.6A shielded
 - RJ45 module KS-T 1/8 Cat. 6/EA tool-less shielded
 - RJ45 module KS-TS 1/8 Cat. 6/EA tool-less shielded
 - RJ45 module KS-T Plus 1/8 Cat. 6A tool-less shielded
- For information on the properties of the module: see data sheet of the requested module.

Versions

Material number	Product	Colour	Weight [kg]	Packing unit
417503	AP Wall outlet IP44, surface mounted, for 2x Key-stone module (delivery without modules)	light grey	0.28 kg	1 pc.