


Data sheet

ID	BSSL WH
Description	rigid conduit, plain ends
Properties	light compression resistance, light impact resistance
Colour	light grey, similar to RAL 7035
Fire Behaviour	non flame propagating
Classification	22211



Compressive strength	Impact strength	Operating temperature	Bending strength	UV-Level
Light (Class 2)	Light (Class 2)	-5 to +60 °C	Rigid	L2

Art. no.	Outer diameter	Inner diameter	Small Package	Large Package
035 319	16 mm	13,7 mm	3 m	90 m
061 882	20 mm	17,4 mm	3 m	90 m
061 884	25 mm	22,1 mm	3 m	90 m

Areas of Recommended Application

Area	
Flush mounted (plaster)	True
Surface mounted	True
Suitable for concrete installation	False
Machine and systems installation	False
Suitable for subsurface installation (screed))	True
Outdoor installation	False
Suitable for installation on wood	False
Hollow wall	True
Underground installation	False

Further technical details

Details	
Halogen free	False
High conducting inner coating	True
With sleeve	False
Fire retardant version	True
Material	PVC-U

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.