

Data sheet

ID	FXKVS SW 6M
Description	double-walled ducting
Properties	corrugated exterior, smooth interior, including one coupler medium resistance against compression, normal impact resistance
Colour	black, similar to RAL 9005
Fire Behaviour	flame propagating
Classification	N 450, IP 40



Norms: ÖVE/ÖNORM EN 61386-1:2009, ÖVE/ÖNORM EN 61386-24:2011



Length	Operating temperature	UV-Level
6 m	-30 bis +70 °C	L2

Art. no.	Inner diameter	Outer diameter	Small Package	Large Package
099 354	41 mm	50 mm	6 m	1170 m
025 751	52 mm	63 mm	6 m	1260 m
025 752	61 mm	75 mm	6 m	978 m
041 193	75 mm	90 mm	6 m	648 m
041 205	93 mm	110 mm	6 m	402 m
041 194	107 mm	125 mm	6 m	288 m
041 196	136 mm	160 mm	6 m	198 m
044 965	150 mm	175 mm	6 m	264 m
041 197	170 mm	200 mm	6 m	120 m

Further technical details

Details	
Model	Rigid
Shape	Outer side ribbed, inner side plain
Surface protection	Untreated
Transparent	False
Material	PE

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.