

FXKVM, nasouvací spojka; černá(RAL 9005), pro
pískotěsné spojení trubek FXKVS nebo FXKVR



materiál	tepl. rozsah
PE	-25°C/+60°C

typ	dn	vb	ref.č.
FXKVM 50	50,0	100	025 755
FXKVM 63	63,0	60	025 756
FXKVM 75	75,0	37	025 757
FXKVM 90	90,0	22	025 758
FXKVM 110	110,0	12	025 102
FXKVM 125	125,0	12	032 331
FXKVM 160	160,0	8	025 759
FXKVM 175	175,0	1	041 351
FXKVM 200	200,0	1	040 801

FXKVDR, těsnící kroužek; černý(RAL 9005), pro
vdotěsné spojení trubek FXKVS nebo FXKVR



materiál	tepl. rozsah
TPE	-25°C/+60°C

typ	dn	vb	ref.č.
FXKVDR 50	50,0	100	025 763
FXKVDR 63	63,0	100	025 764
FXKVDR 75	75,0	100	025 765
FXKVDR 90	90,0	100	025 766
FXKVDR 110	110,0	100	025 458
FXKVDR 125	125,0	100	032 329
FXKVDR 160	160,0	100	025 767
FXKVDR 175	175,0	100	055 219
FXKVDR 200	200,0	100	040 799

FXKVDR, tesniaci krúžok; čierny (RAL 9005), pre
vodo-tesné spojenie FXKVS, alebo FXKVR rúr



Přivaděč na most Apolo Bratislava
Privádzač na most Apolo Bratislava