



UCB3015

Name: **Cubo X Ex Combo box**

Size 400 x 250+25 x 200 mm, drilling area 270 x 110, minimum installing space 300 x 140

Type: UCB3015

EAN: 6438100156268

Description: Ensto Cubo X Ex Universal combo boxes
Universal combo box is an Ex e enclosure designed to fix perfectly next to an Ex d enclosure. Instead of having one Ex d enclosure with terminals and human interface you can have light-weight and flexible solution. Each combo junction box will be custom made according to customer terminal and hole specifications.




Photo presented is indicative only

Package: 1

Unit: PCS



Technical specification

Certificates DNV 11 ATEX 98913X, IECEx DNV 11.0006X

Ratings

Degree of protection IP66

Power 17.8 W

Dimensions

Height 275 mm

Width 400 mm

Depth 200 mm

Size 400 x 250+25 x 200

Temperatures

Ambient temperature -55°C up to +40°C

Optional temprature class T6 / T5 / T4 (+40°C / +55°C / +65°C)

Temperature class T6 [T85°C]

Features

Mounting Connection to enclosure by bolts

Materials

Material Stainless steel AISI 316L, Stainless steel AISI 316L

Surface treatment Brushed

Certificates

Standards EN 60079-0:2009, EN 60079-0:2012, EN 60079-31:2009, EN 60079-7:2007, IEC 60079-0:2007, IEC 60079-0:2011, IEC 60079-31:2008, IEC 60079-7:2006, IEC 60079-7:2007



Saves Your Energy

PRODUCT CARD

11.3.2015

2/2

UCB3015

Standard markings

II 2 G Ex IIC Gb, II 2 D Ex tb IIIC T_a °C Db IP66

Ensto Finland Oy

Ensio Miettisen katu 2
P.O.Box 77
06101 Porvoo, Finland

Tel. +358 204 76 21
Fax +358 204 76 2516

www.ensto.com