

Accessories

761501

**Indicator and operating module LRS 110 - ESSER, German****Approval: VdS**

For displaying the current smoke density and the alarm level of the LRS 100 detector unit and the LRS compact/net. In addition, the alarm and fault status are shown by LEDs. Different functions e.g. buzzer off and reset can be controlled via the key pad. The unit is also equipped with 7 freely configurable, floating contacts.

Technical Data

Operating voltage	18 ... 30 V DC
Current consumption	110 ... 130 mA
Connection terminal	Ø 0,2 ... 2,5 mm ²
Ambient temperature	0 °C ... 39 °C
Type of protection	IP30
Housing	metal
Color	gray, similar to RAL 7035
Weight	approx. 1 kg
Dimensions	W: 140 mm H: 150 mm D: 90 mm



As the LRS compact/net recognises up to three alarm states, the LED's for main alarm 1 and main alarm 2 are activated jointly.

For flush mounting, order kit with Part No. 761511 separately.

Programming via interfaced network.

762401

**Indicator and operating module LRS 110 - ESSER, English****Approval: VdS**

For displaying the current smoke density and the alarm level of the LRS 100 detector unit and the LRS compact/net. In addition, the alarm and fault status are shown by LEDs. Different functions e.g. buzzer off and reset can be controlled via the key pad. The unit is also equipped with 7 freely configurable, floating contacts.



As the LRS compact/net recognizes up to three alarm states, the LEDs for main alarm 1 and main alarm 2 are activated jointly.

For flush mounting, order kit with Part no. 761511 separately.

Programming via interfaced network.

762411

**Indicator and operating module LRS 110 - ESSER, French**

As 761501, but ESSER - French

Technical Data

Operating voltage	18 ... 30 V DC
Current consumption	110 ... 130 mA
Connection terminal	Ø 0,2 ... 2,5 mm ²
Ambient temperature	0 °C ... 39 °C
Type of protection	IP30
Housing	metal
Color	gray, similar to RAL 7035
Weight	approx. 1000 g
Detector specification	EN 54-20
Dimensions	W: 140 mm H: 150 mm D: 90 mm



As the LRS compact/net recognizes up to three alarm states, the LEDs for main alarm 1 and main alarm 2 are activated jointly.

For flush mounting, order kit with Part No. 761511 separately.

Programming via interfaced network.

762421

**Indicator and operating module LRS 110 - ESSER, Italian**

As 761501, but - ESSER, Italian.

762431

**Indicator and operating module LRS 110 - ESSER, Spanish**

As 761501, but - ESSER, Spanish.