



Category 5e Unshielded Twisted Pair (UTP) 25x50mm shuttered, moulded, modules (Euro Mod) conform to class D performance. They feature a slim line design, which is an ideal solution for shallow floor box or dado trunking Applications.

Each module is supplied with a slide in label area, for easy and clear outlet identification, and a mini cable-tie. Suits British standard faceplates only.

Features

- > Complete shuttered module with PCB technology
- > Slim line design for shallow Applications
- > IDC punch down
- > Wiring diagram and mini cable tie supplied
- > Supplied in boxes of 20pcs
- > Compatible with Optronics UK faceplates

Technical Specifications

MECHANICAL	VALUE
Housing Material	PC UL94V-0
IDC Material	Phosphor Bronze Stamp Pin 0.35mm
Contact Material	Phosphor Bronze + Gold Plating 0.50mm
RJ45 Jack Life	Min 750 Insertions
IDC Life	Min 250 Terminations

Applications

- > Supports category 5e (class D) networks running up to 100 MHz applications

Conformance

- > Category 5e
- > ANSI/EIA/TIA 568B.2 : 2002
- > ISO/IEC 11801 : 2002
- > RoHS
- > UL approved

Ordering Information

DESCRIPTION	PART NUMBER
Category 5e Unshielded Twisted Pair (UTP) 50x25mm Shuttered Moulded Module White - Box of 20pcs - UL approved	CAT5EFACEMODULE