

SPRINT ATEX cable glands, metric, stainless steel 1.4305



Explosion protection: II 2 G Ex e II

II 2 D Ex tD A21 IP68

Certificates: PTB 05 ATEX 1098 X

Protection class to EN 60 529: IP 68 to 5 bar (30 min)

Protection class to DIN 40 050-T9: IP 69K

Temperature range: -40°C to 75°C

Material: - Cable gland: stainless steel A2 (1.4305)(X10CrNiS 18 9 / AISI 303)

- Clamping cage: polyamide

- Gasket: EPDM


Equipment: - Maximum traction relief through WISKA patent lamella

- Seal-tight to enclosure rack through additional EPDM sealing ring

- Same sealing range on all SPRINT-glands

- Incl. dust-protection gasket

SPRINT ATEX Kabelverschraubungen, metrisch, Edelstahl 1.4305



Explosionsschutz: II 2 G Ex e II

II 2 D Ex tD A21 IP68

Bescheinigungen: PTB 05 ATEX 1098 X

Schutzart gemäß EN 60 529: IP 68 bis 5 bar (30 min)

Schutzart gemäß DIN 40 050-T9: IP 69K

Einsatztemperatur: -40°C bis 75°C

Material: - Verschraubung: Edelstahl A2 (1.4305) (X10CrNiS 18 9 / AISI 303)

- Klemmkäfig: Polyamid

- Dichtung: EPDM

Ausstattung: - Optimale Abdichtung und Zugentlastung durch patentiertes WISKA-Lamellensystem

- Abdichtung an Gehäuse durch zusätzlichen EPDM O-Ring

- Gleiche Dichtbereiche und Schlüsselweiten für alle SPRINT-Verschraubungen

- Lieferung mit Staubschutzscheibe

Type	WISKA-No.						TL
			mm	mm	mm	mm	mm
ESSKE 12	10069200	10	M 12x1,5	5	4 · 7	17	23 · 30
ESSKE 16	10069201	10	M 16x1,5	5	5 · 10	22	26 · 34
ESSKE 20	10069202	10	M 20x1,5	6	6 · 13	24	29 · 37
ESSKE 25	10069203	10	M 25x1,5	7	10 · 17	30	33 · 42
ESSKE 32	10069204	5	M 32x1,5	8	13 · 21	36	36 · 44
ESSKE 40	10069205	5	M 40x1,5	8	16 · 28	46	44 · 55
ESSKE 50	10069206	2	M 50x1,5	9	21 · 35	55	51 · 62
ESSKE 63	10069207	1	M 63x1,5	10	34 · 48	68	56 · 67

Recommended accessories:

Empfohlenes Zubehör:



ESMU

Page / Seite 106