


SPRINT EMC cable glands, metric, earthing cones DIN 89345, stainless steel 1.4404

SPRINT EMV Kabelverschraubungen, metrisch, Erdungseinsatz DIN 89345, Edelstahl 1.4404



Protection class to EN 60 529: IP 68 to 5 bar (30 min)

Protection class to DIN 40 050-T9: IP 69K

Temperature range: -40°C to 100°C, interm. up to approx. 120°C
Material: - Cable gland: Stainless steel A4 (1.4404) (X2CrNiMo 17 12 2 / AISI 316L)

- Clamping cage: polyamide
- Gasket: EPDM

Equipment: - EMC gland with inserts according to DIN 89345

- Continuous EMC protection due to earthing cones
- Maximum traction relief through WISKA patent lamella
- Seal-tight to enclosure rack through additional EPDM sealing ring
- Same sealing range and on all SPRINT-glands

Schutzart gemäß EN 60 529: IP 68 to 5 bar (30 min)

Schutzart gemäß DIN 40 050-T9: IP 69K

Einsatztemperatur: -40°C bis 100°C, kurzzeitig bis ca. 120°C

Material: - Verschraubung: Edelstahl A4 (1.4404) (X2CrNiMo 17 12 2 / AISI 316L)

- Klemmkäfig: Polyamid
- Dichtung: EPDM

Ausstattung: - EMV-Verschraubung mit Innenteilen nach DIN 89345

- Dauerhafte Kontaktierung des Schirmgeflechts durch Erdungskonen
- Optimale Abdichtung Zugentlastung durch patentiertes WISKA-Lamellensystem
- Abdichtung am Gehäuse durch zusätzlichen EPDM O-Ring
- Gleiche Dichtbereiche und Schlüsselweiten für alle SPRINT-Verschraubungen

Type	WISKA-No.							TL
			mm	mm	mm	mm	mm	mm
ESSKV-4 12 EMV-Z	10069116	10	M 12x1,5	5	3 · 7	5	17	23 · 30
ESSKV-4 16 EMV-Z	10069117	10	M 16x1,5	5	4,5 · 10	6	22	26 · 34
ESSKV-4 20 EMV-Z	10069118	10	M 20x1,5	6	6 · 13	7	24	29 · 37
ESSKV-4 25 EMV-Z	10069119	10	M 25x1,5	7	9 · 17	14	30	33 · 42
ESSKV-4 32 EMV-Z	10069120	5	M 32x1,5	8	13 · 21	18	36	36 · 44
ESSKV-4 40 EMV-Z	10069121	5	M 40x1,5	8	16 · 28	24	46	44 · 55
ESSKV-4 50 EMV-Z	10069122	2	M 50x1,5	9	21 · 35	30	55	51 · 62
ESSKV-4 63 EMV-Z	10069123	1	M 63x1,5	10	34 · 48	39	68	56 · 67