


ATEX cable glands, metric, hexagonal, type Z

ATEX Kabelverschraubungen, metrisch, 6-Kant, Typ Z



Explosion protection: II 2 G Ex e II
Certificates: PTB 03 ATEX 1156 X
Protection class to EN 60 529: Without o-ring IP 54; with o-ring IP 56
Temperature range: -40°C to 100°C
Material: Cable gland: brass; gasket: EPDM
Equipment: - Economy Ex e gland according to DIN 89280 for shielded cable, equipment Z
 - Nickel-plated and chromium-plated on request



Explosionsschutz: II 2 G Ex e II
Bescheinigungen: PTB 03 ATEX 1156 X
Schutzart gemäß EN 60 529: Ohne O-Ring IP 54; mit O-Ring IP 56
Einsatztemperatur: -40°C bis 100°C
Material: Verschraubung: Messing; Dichtung: EPDM
Ausstattung: - Einfache Ex e Verschraubung nach DIN 89280 für geschirmte Kabel
 - Auch vernickelt und verchromt lieferbar

Type	WISKA-No. length / blank					TL	
			mm	mm	mm	mm	
EX-KVM-18-Z-08	10030002	1	M 18x1,5	10	7,0 · 8,5	24	40 · 43
EX-KVM-18-Z-10	10030003	1	M 18x1,5	10	8,0 · 10,5	24	40 · 43
EX-KVM-20-Z-08	10030006	1	M 20x1,5	10	7,0 · 8,5	24	40 · 43
EX-KVM-20-Z-10	10030007	1	M 20x1,5	10	8,0 · 10,5	24	40 · 43
EX-KVM-24-Z-08	10030014	1	M 24x1,5	11	7,0 · 8,5	29	43 · 47
EX-KVM-24-Z-10	10030015	1	M 24x1,5	11	8,0 · 10,5	29	43 · 47
EX-KVM-24-Z-12	10030016	1	M 24x1,5	11	10,0 · 12,5	29	43 · 47
EX-KVM-24-Z-14	10030017	1	M 24x1,5	11	12,0 · 14,5	29	43 · 47
EX-KVM-24-Z-16	10030018	1	M 24x1,5	11	14,0 · 16,5	29	43 · 47
EX-KVM-24-Z-17	10030019	1	M 24x1,5	11	16,0 · 17,5	29	43 · 47
EX-KVM-25-Z-08	10030026	1	M 25x1,5	11	7,0 · 8,5	29	43 · 47
EX-KVM-25-Z-10	10030027	1	M 25x1,5	11	8,0 · 10,5	29	43 · 47
EX-KVM-25-Z-12	10030028	1	M 25x1,5	11	10,0 · 12,5	29	43 · 47
EX-KVM-25-Z-14	10030029	1	M 25x1,5	11	12,0 · 14,5	29	43 · 47
EX-KVM-25-Z-16	10030030	1	M 25x1,5	11	14,0 · 16,5	29	43 · 47
EX-KVM-25-Z-17	10030031	1	M 25x1,5	11	16,0 · 17,5	29	43 · 47
EX-KVM-30-Z-18	10030034	1	M 30x2	12	16,0 · 18,5	36	49 · 53
EX-KVM-30-Z-20	10030035	1	M 30x2	12	18,0 · 20,5	36	49 · 53
EX-KVM-32-Z-18	10030038	1	M 32x2	12	16,0 · 18,5	36	49 · 53
EX-KVM-32-Z-20	10030039	1	M 32x2	12	18,0 · 20,5	36	49 · 53