


Cable glands, PG, circular, Typ Z, thread to DIN 40430

Kabelverschraubungen, PG, Typ Z, Gewinde nach DIN 40430



Protection class to EN 60 529: IP 54; installation with connection thread gasket IP 66
Temperature range: -40°C to 100°C, interm. up to approx. 120°C
Material: - Cable gland: brass (nickel-plated or chromium-plated on request)
 - Gasket: EPDM
Equipment: Cable gland according to DIN 89280 for armoured cable

Schutzart gemäß EN 60 529: IP 54; bei Montage mit Anschlussgewindedichtring IP 66
Einsatztemperatur: -40°C bis 100°C, kurzzeitig bis 120°C
Material: - Verschraubung: Messing blank (vernickelt oder verchromt auf Anfrage)
 - Dichtung: EPDM
Ausstattung: Kabeleinführung nach DIN 89280 aus Messing für geschirmte Kabel

Type	WISKA-No. bright / blank						TL
			mm	mm	mm	mm	mm
KVMP 18/9-Z8	10010911	1	PG 9	8	7 · 8,5	19	41
KVMP 18/9-Z10	10012768	1	PG 9	8	8 · 10,5	19	41
KVMP 24/9-Z12	10010924	1	PG 9	9	10 · 12,5	24	47
KVMP 18/11-Z8	10010912	1	PG 11	8	7 · 8,5	19	41
KVMP 18/11-Z10	10010914	1	PG 11	8	8 · 10,5	19	41
KVMP 24/11-Z12	10010931	1	PG 11	9	10 · 12,5	24	47
KVMP 24/11-Z14	10010932	1	PG 11	9	12 · 14,5	24	47
KVMP 18/13,5-Z8	10010915	1	PG 13,5	8	7 · 8,5	19	41
KVMP 18/13,5-Z10	10010917	1	PG 13,5	8	8 · 10,5	19	41
KVMP 24/13,5-Z12	10010938	1	PG 13,5	9	10 · 12,5	24	47
KVMP 24/13,5-Z14	10010939	1	PG 13,5	9	12 · 14,5	24	47
KVMP 18/16-Z8	10010918	1	PG 16	8	7 · 8,5	19	41
KVMP 18/16-Z10	10010920	1	PG 16	8	8 · 10,5	19	41
KVMP 24/16-Z12	10010945	1	PG 16	9	10 · 12,5	24	47
KVMP 24/16-Z14	10010946	1	PG 16	9	12 · 14,5	24	47
KVMP 24/16-Z16	10010947	1	PG 16	9	14 · 16,5	24	47
KVMP 24/16-Z17	10010948	1	PG 16	9	16 · 17,5	24	47
KVMP 24/21-Z12	10010952	1	PG 21	9	10 · 12,5	24	47
KVMP 24/21-Z14	10010953	1	PG 21	9	12 · 14,5	24	47
KVMP 24/21-Z16	10010954	1	PG 21	9	14 · 16,5	24	47
KVMP 24/21-Z17	10010955	1	PG 21	9	16 · 17,5	24	47

Cable glands, PG, circular, Typ Z, thread to DIN 40430

Kabelverschraubungen, PG, Typ Z, Gewinde nach DIN 40430

Type	WISKA-No. bright / blank						TL
			mm	mm	mm	mm	mm
KVMP 30/21-Z18	10010969	1	PG 21	10	16 · 18,5	30	51
KVMP 30/21-Z20	10010970	1	PG 21	10	18 · 20,5	30	51
KVMP 30/29-Z18	10010971	1	PG 29	10	16 · 18,5	30	51
KVMP 30/29-Z20	10010972	1	PG 29	10	18 · 20,5	30	51
KVMP 36/29-Z22	10010984	1	PG 29	11	20 · 22,5	36	56
KVMP 36/29-Z24	10010985	1	PG 29	11	22 · 24,5	36	56
KVMP 36/29-Z26	10010986	1	PG 29	11	24 · 26,5	36	56
KVMP 36/36-Z22	10010988	1	PG 36	11	20 · 22,5	36	56
KVMP 36/36-Z24	10010989	1	PG 36	11	22 · 24,5	36	56
KVMP 36/36-Z26	10010990	1	PG 36	11	24 · 26,5	36	56
KVMP 45/36-Z28	10011001	1	PG 36	11	26 · 28,5	46	59
KVMP 45/36-Z30	10011002	1	PG 36	11	28 · 30,5	46	59
KVMP 45/36-Z32	10011003	1	PG 36	11	30 · 32,5	46	59
KVMP 45/42-Z30	10011005	1	PG 42	11	28 · 30,5	46	59
KVMP 45/42-Z32	10011006	1	PG 42	11	30 · 32,5	46	59
KVMP 56/42-Z35	10011013	1	PG 42	12	32 · 35,5	55	65
KVMP 56/42-Z38	10011014	1	PG 42	12	35 · 38,5	55	65
KVMP 56/42-Z41	10011015	1	PG 42	12	38 · 41,5	55	65
KVMP 56/48-Z38	10011017	1	PG 48	12	35 · 38,5	55	65
KVMP 56/48-Z41	10011018	1	PG 48	12	38 · 41,5	55	65
KVMP 72/48-Z44	10011022	1	PG 48	12	41 · 44,5	70	69
KVMP 72/48-Z48	10011023	1	PG 48	12	44 · 48,5	70	69
KVMP 72/48-Z52	10011024	1	PG 48	12	48 · 52,5	70	69

KUNSTSTOFF
PLASTICMEMBRAN
MEMBRANEMESSING
BRASS

DIN 89280

EDELSTAHL
STAINL. STEELEMV
EMC

ATEX

VentGLAND

BS 6121

DICHTUNGEN
SEALINGSWERKZEUGE
TOOLSTECHNIK
TECHNICSINDEX
INDEX