

ATEX Ex d cable glands for non armoured cables, metric

ATEX Ex d Kabelverschraubungen für ungeschirmte Kabel, metrisch



Explosion protection: II 2 GD EEx d IIC/EEx e II

Certificates: Nemko 03 ATEX 1460X

Protection class to EN 60 529: IP 67

Temperature range: -40°C to 100°C


Material: Brass nickel-plated

Equipment: - Ex d cable gland for non armoured cable, single compression at outer jacket of cable

- Stainless steel on request

- Available with earth tag and shroud

- Ex d IIC only for housings with lower or equal internal volume to 2,000 cm³



Explosionsschutz: II 2 GD EEx d IIC/EEx e II

Bescheinigungen: Nemko 03 ATEX 1460X

Schutzart gemäß EN 60 529: IP 67

Einsatztemperatur: -40°C bis 100°C

Material: Messing vernickelt

Ausstattung: - Ex d Kabelverschraubung für unarmierte Kabel, Abdichtung am Außenmantel des Kabels

- Edelstahl auf Anfrage

- Lieferbar mit Erdungsscheibe und Schrumpfschlauch

- Ex d IIC nur für Gehäuse mit einem kleineren oder gleichen Innenvolumen von 2.000 cm³

Type	WISKA-No. Ni					
			mm	mm	mm	mm
OSNJ A2F-16a	50065500	1	M 16x1,5	15	3 - 6	24
OSNJ A2F-16b	50065501	1	M 16x1,5	15	6,1 - 10	24
OSNJ A2F-20a	50065502	1	M 20x1,5	15	10 - 13	27
OSNJ A2F-20b	50065503	1	M 20x1,5	15	13,1 - 15	27
OSNJ A2F-25a	50065504	1	M 25x1,5	15	15,1 - 16	32
OSNJ A2F-25b	50065505	1	M 25x1,5	15	16,1 - 18	32
OSNJ A2F-32a	50065506	1	M 32x1,5	15	18,1 - 22	39
OSNJ A2F-32b	50065507	1	M 32x1,5	15	22,1 - 26	39
OSNJ A2F-40a	50065508	1	M 40x1,5	15	26,1 - 28	48
OSNJ A2F-40b	50065509	1	M 40x1,5	15	28,1 - 32	48
OSNJ A2F-50a	50065510	1	M 50x1,5	15	32,1 - 34	58
OSNJ A2F-50b	50065511	1	M 50x1,5	15	34,1 - 40	58
OSNJ A2F-63a	50065512	1	M 63x1,5	15	40,1 - 44	73
OSNJ A2F-63b	50065513	1	M 63x1,5	15	44,1 - 50	73
OSNJ A2F-63c	50065514	1	M 63x1,5	15	50,1 - 54	73
OSNJ A2F-75a	50065515	1	M 75x1,5	20	54,1 - 56	85
OSNJ A2F-75b	50065516	1	M 75x1,5	20	56,1 - 60	85
OSNJ A2F-75c	50065517	1	M 75x1,5	20	60,1 - 62	85
OSNJ A2F-75d	50065518	1	M 75x1,5	20	62,1 - 66	85