


WIRE CONNECTORS

2,5 mm²

Wire connector with a 3 mm wide wire entry and terminal screws M 3,5. The tightening torque 0,8–1,0 Nm. Easy to cut by hand to the desired pole number.


ARTICLE	APPROVAL CODE	RECOMMENDED NUMBER OF WIRES, PCS/MM ²	WEIGHT (G)	PACKAGE QTY
AL1.12	AL1	[2 / 4] [3 / 2,5] [4 / 1,5]	53	10 / 50



6 mm²

Wire connector with a 4 mm wide wire entry and terminal screws M 4,5. The tightening torque 1,8–2,0 Nm. Easy to cut by hand to the desired pole number.


ARTICLE	APPROVAL CODE	RECOMMENDED NUMBER OF WIRES, PCS/MM ²	WEIGHT (G)	PACKAGE QTY
AL2.12	AL2	[2 / 6] [3 / 4] [4 / 2,5]	82	10 / 50



10 mm²

Wire connector with a 5,5 mm wide wire entry and terminal screw M 6. The tightening torque 2,5–2,7 Nm.


ARTICLE	APPROVAL CODE	RECOMMENDED NUMBER OF WIRES, PCS/MM ²	WEIGHT (G)	PACKAGE QTY
AL13	AL13	[2 / 10] [3 / 6] [4 / 6] [4 / 4]	14	100 / 500



2,5 mm²

Wire connector with a 4,2 mm wide wire entry and terminal screws M 4. The tightening torque 1,2–1,4 Nm. Easy to cut by hand to the desired pole number.

ARTICLE	APPROVAL CODE	RECOMMENDED NUMBER OF WIRES, PCS/MM ²	WEIGHT (G)	PACKAGE QTY
KD 160.01	1617-01	[4 / 1] [3 / 1,5] [2 / 2,5]	2	100 / 1 000
KD 160.12	1617-12	[4 / 1] [3 / 1,5] [2 / 2,5]	25	500



4 mm²

Uncuttable wire connector with two wire entries, 4,2 mm, screw M 4. Ideal for cables with a great number of wires. The tightening torque 1,2–1,4 Nm.

ARTICLE	APPROVAL CODE	RECOMMENDED NUMBER OF WIRES, PCS/MM ²	WEIGHT (G)	PACKAGE QTY
KD 42001	1630	[2 X 2 / 2,5] [2 X 2 / 4] [2 X 3 / 1,5] [2 X 4 / 1]	7	100 / 1 000

