

ENSTO

KA241.12

Terminal strip

Code KA241.12
GTIN 6418677103445
ENumber
Name Terminal strip Ensto Clampo
12-pole
Description Terminal block with flat base. Mounting hole Ø 3.5 mm. Terminal screw M 3. Terminal block can be ordered precut to desired number of poles. On request individual pole positions can be marked with desired markings. To order imprinting please specify the characters on your order. Turret or ledge marking available.
Vendor Ensto Finland Oy
® CE ENEC EAC



Technical specification

Technical specification

UL Cat.No.: 241.12-AK

Dimensions

Weight: 32.0 g
Conductor cross-section: 4 mm²
Dimensions l x w x h: 117x22,2x15,8
Diameter of mounting hole: 3.5 mm

Temperatures

Max. operating temperature: +100 °C

Electrical values

CSA: 241-12
CSA Rated current: 30 A
CSA Rated voltage: 300 V

CSA Wire range: 18-12 AWG

Materials

Material: Polyamide 6

Features

Number of poles: 12

Mechanical

Tightening torque: 0.6 Nm

Certificates

UL File no.: E103245

Ratings

Rated voltage: 450 V

ETIM 7: EC001284 Single- and multi-pole terminal strip

ETIM

ETIM

Length: 22 mm

Closing plate required: false

Material insulation body: Thermoplastic

Rated voltage: 450 V

Width/grid dimension: 10 mm

Mounting method: Direct mounting

Number of poles: 12

Colour: White

Type of electrical connection 1: Screw connection

Number of clamp positions per pole: 2

Height at lowest possible mounting height: 16 mm

Operation temperature: 80 °C

Connectable conductor cross section fine-strand with cable end sleeve: 1.5 ... 4 mm²

Connectable conductor cross section solid-core: 1.5 ... 4 mm²

Connectable conductor cross section fine-strand without cable end sleeve: 1.5 ... 4 mm²

Explosion-tested version 'Ex e': false

Connectable conductor cross section multi-wired: 1.5 ... 4 mm²

Inflammability class of insulation material acc. with UL94: V2

Rated current I_n: 30 A

Transparent: true

Type of electrical connection 2: Screw connection

Connection position: Sideways

Drill hole distance centrically: 10 mm

Packaging

Default package

Unit:	PCS
Size:	250
Length:	385 mm
Width:	260 mm
Height:	130 mm
Weight (net):	8 kg
Weight (brt):	8.25 kg
Volume:	13.013

Pallet package

Unit:	PCS
Size:	15750
Length:	1200 mm
Width:	800 mm
Height:	1060 mm
Weight (brt):	544.8 kg
Volume:	1017.6

