Product updated on October 17, 2018

CAT3 UTP 1U PCB Patch Panel with Cable Manager





Category 3 high density voice patch panels offer a cost effective method for integrating voice circuits into standard structured cabling systems. Available in both 25 and 50 ports on a 1U 19" footprint, ideal for maximizing rack space.

FEATURES/BENEFITS

- 19" rack mountable
- Accepts 26-23 AWG
- Catogory 3
- · Supplied with fixings and earth wire
- IDC punch down
- 25 or 50 RJ45 ports on 1U footprint
- Integral cable management and grounding clamps

APPLICATIONS

- Voice integration into standard structured cabling systems
- ANSI/TIA-568-C.2
- ISO/IEC 11801.2:2010
- ISO/IEC 60603-7 compliant
- RoHS 2002/95/EC cmpliant

SPECIFICATIONS

Electrical	Value	
Current Rating	1.5 Amp	
Insulation Resistance	≥ 500m ohm	
Contact Resistance	≤ 10m ohm	
DC Resistance	≤ 0.1 ohm	
DC/AC Volt endurance	DC1000V/AC750V 1min	
Insertion Life	≥750	
Termination Cycle	≥200	
Operating Temperature	-10 to +60°c	
Operating Humidity	10 to 90% RH	
Storage Temprature	-40 to 68°c	
Plastic components	High impact flame retardant plastic	
UL	UL94V-0	

ORDERING INFORMATION

DESCRIPTION	PART NO.	Optronics PN*
AFL Hyperscale® CAT3 UTP 1U 25port PCB Patch Panel with Cable Manager 30 mic gold plated	UPP211111	300-012
AFL Hyperscale® CAT3 UTP 1U 50port PCB Patch Panel with Cable Manager 30 mic gold plated	UPP211112	300-013

*Note: Optronics product is going to be phase-out.



FURTHER INFORMATION

- For additional information please contact your sales representative
- To view the product 360 visit the product page (Scan the QR code or visit the link below)
- Downloaded from https://www.aflhyperscale.com/product/cat-3-voice-patch-panel-1
- · AFL Hyperscale reserves the right to make changes in this datasheet at any time without notice
- Information in this document is correct as of October 17, 2018

SCAN QR FOR PRODUCT PAGE

mesales@aflhyperscale.com

+971 4 404 9606

India

+44 (0) 1908 441 144 emeasales@aflhyperscale.com © AFL Hyperscale 2018