
Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



AX101943 Faceplates and Panels - FiberExpress Manager 1U Rack Mount Patch Panel, 19 in







For more Information please call

1-800-Belden1



FiberExpress Manager 1U Rack Mou	ınt Patch Panel, 19 in, Empty
Jsage (Overall)	
Suitable Applications:	FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room
Related Parts:	FiberExpress Manager Connector Module, Splice Holder Kit, Flex Kit, Offset Bracket Kit, Cable Mgnt accessory
Physical Characteristics (Connectivity)	
Capacity Max. Capacity:	3 FiberExpress Manager Connector Module
Access	3 i iber Express Manager Confirection Module
Front Connection:	1 inch Pullout
Dimensions Dimensions:	
Height (mm) Width (mm) Depth (mm) 44.450 482.600 304.800	
Materials Materials:	
Description Material Panel Steel	
Color	
Color:	Black
Weight	
Weight:	4.990 kg
Included Parts Included Parts:	labels, screws, velcro straps, cable ties, installation sheet
Packaging Packaging:	Individually packaged in a cardboard box.
Mechanical Characteristics (Connectivity)	
Storage Temperature Range:	-40°C To +70°C
Operating Temperature Range:	-10°C To +60°C
Applicable Specifications and Agency Comp	
Applicable Standards & Environmental Programs	
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/10/2008
MII Order #39 (China RoHS):	EUP 50
Safety Listing:	ACA
Suitability	
Suitability - Indoor:	Yes
Transmission Characteristics (Connectivity)	
Notes (Overall)	
Notes: For proper installation refer to Installation Guide	e PX103293 included with the product or visit our web site at http://www.belden.com
Product Family	
Put Ups and Colors:	
Item# Putup Ship Weight	Color Notes Item Desc

Page 1 of 2 08-26-2016

Detailed Specifications & Technical Data





AX101943 Faceplates and Panels - FiberExpress Manager 1U Rack Mount Patch Panel, 19 in

AX101943	1 EA	16.032 LB		FXM 1U RACK MOUNT PATCHP

Revision Number: 0 Revision Date: 06-04-2009

© 2016 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/5FC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2