



**Product:** [2413](#) 

CAT6+ Horizontal, 4pr, UTP, LS-PVC Jkt, CMP

### Product Description

CAT6+ (350MHz), 4-Pair, U/UTP-unshielded, Plenum-CMP, Premise Horizontal cable, 23 AWG solid bare copper conductors, dual FRPO/FEP insulation, tape separator, ripcord, Flamarrest® jacket

### Technical Specifications

#### Product Overview

Suitable Applications:	Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155 ATM, 622 ATM, 250MHz Category 6
------------------------	--

#### Physical Characteristics (Overall)

**Conductor**

AWG	Stranding	Material	No. of Pairs
23	Solid	BC - Bare Copper	4
Conductor Count:			8
Total Number of Pairs:			4

**Insulation**

Material	
FRPO/FEP - Flame Retardant Polyolefin/Fluorinated Ethylene Propylene	
Bonded-Pair:	N/A

**Color Chart**

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

**Outer Jacket Material**

Material	Material Trade Name	Nominal Diameter	Ripcord	Separator Material
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.224 in	Yes	Patented Dielectric Tape

#### Electrical Characteristics

**Conductor DCR**

Max. Conductor DCR	Max. DCR Unbalance
78 Ohm/km	3 %

**Capacitance**

Max. Capacitance Unbalance	Nom. Mutual Capacitance
330 pF/100m	17 pF/ft

**Delay**

Frequency [MHz]	Max. Delay	Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
100 MHz	537.6 ns/100m	35 ns/100m	72 %

## High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Max./Min. Input Impedance (unFitted)	Max./Min. Fitted Impedance
1 MHz	2.0 dB/100m	75.3 dB	75.3 dB	73.3 dB	73.3 dB	70.8 dB	67.8 dB	20.0 dB	100 ± 15 Ohm	102 ± 15 Ohm
4 MHz	3.7 dB/100m	66.3 dB	66.3 dB	62.6 dB	62.6 dB	58.8 dB	55.8 dB	23.0 dB	100 ± 15 Ohm	100 ± 15 Ohm
8 MHz	5.2 dB/100m	61.8 dB	61.8 dB	56.6 dB	56.6 dB	52.7 dB	49.7 dB	24.5 dB	100 ± 15 Ohm	100 ± 15 Ohm
10 MHz	5.8 dB/100m	60.3 dB	60.3 dB	54.5 dB	54.5 dB	50.8 dB	47.8 dB	25.0 dB	100 ± 15 Ohm	100 ± 15 Ohm
16 MHz	7.4 dB/100m	57.2 dB	57.2 dB	49.9 dB	49.9 dB	46.7 dB	43.7 dB	25.0 dB	100 ± 15 Ohm	100 ± 15 Ohm
20 MHz	8.3 dB/100m	55.8 dB	55.8 dB	47.5 dB	47.5 dB	44.8 dB	41.8 dB	25.0 dB	100 ± 15 Ohm	100 ± 15 Ohm
25 MHz	9.3 dB/100m	54.3 dB	54.3 dB	45.1 dB	45.1 dB	42.8 dB	39.8 dB	24.3 dB	100 ± 15 Ohm	100 ± 15 Ohm
31.25 MHz	10.4 dB/100m	52.9 dB	52.9 dB	42.5 dB	42.5 dB	40.9 dB	37.9 dB	23.6 dB	100 ± 15 Ohm	100 ± 15 Ohm
62.5 MHz	15.0 dB/100m	48.4 dB	48.4 dB	33.4 dB	33.4 dB	34.9 dB	31.9 dB	21.5 dB	100 ± 15 Ohm	100 ± 15 Ohm
100 MHz	19.3 dB/100m	45.3 dB	45.3 dB	26.0 dB	26.0 dB	30.8 dB	27.8 dB	20.8 dB	100 ± 15 Ohm	100 ± 15 Ohm
155 MHz	24.6 dB/100m	42.4 dB	42.4 dB	17.9 dB	17.9 dB	27.0 dB	24.0 dB	19.5 dB	100 ± 22 Ohm	100 ± 15 Ohm
200 MHz	28.3 dB/100m	40.8 dB	40.8 dB	12.5 dB	12.5 dB	24.8 dB	21.8 dB	18.7 dB	100 ± 22 Ohm	100 ± 15 Ohm
250 MHz	32.1 dB/100m	39.3 dB	39.3 dB	7.2 dB	7.2 dB	22.8 dB	19.8 dB	18.0 dB	100 ± 32 Ohm	100 ± 15 Ohm
300 MHz	35.6 dB/100m	38.1 dB	36.1 dB	2.5 dB	0.5 dB	21.3 dB	18.3 dB	17.5 dB	100 ± 32 Ohm	100 ± 15 Ohm
350 MHz	38.9 dB/100m	37.1 dB	35.1 dB	-1.8 dB	-3.8 dB	19.9 dB	16.9 dB	17.0 dB	100 ± 32 Ohm	100 ± 15 Ohm
400 MHz	42.0 dB/100m	36.3 dB	34.3 dB	-5.7 dB	-7.7 dB	18.8 dB	15.8 dB	16.6 dB	100 ± 32 Ohm	100 ± 15 Ohm
450 MHz	45.0 dB/100m	35.5 dB	33.5 dB	-9.5 dB	-11.5 dB	17.7 dB	14.7 dB	16.2 dB	100 ± 32 Ohm	100 ± 15 Ohm
500 MHz	47.9 dB/100m	34.8 dB	32.8 dB	-13.1 dB	-15.1 dB	16.8 dB	13.8 dB	15.9 dB	100 ± 32 Ohm	100 ± 15 Ohm
550 MHz	50.6 dB/100m	34.2 dB	32.2 dB	-16.4 dB	-18.4 dB	16.0 dB	13.0 dB	15.6 dB	100 ± 32 Ohm	100 ± 15 Ohm

## Voltage

### UL Voltage Rating

300 V RMS

## Temperature Range

Installation Temp Range:	0°C To +50°C
UL Temp Rating:	90°C
Storage Temp Range:	-20°C To +75°C
Operating Temp Range:	-20°C To +75°C

## Mechanical Characteristics

Bulk Cable Weight:	26 lbs/1000ft
Max Recommended Pulling Tension:	25 lbs
Min Bend Radius During Installation:	2.25 in
Min Bend Radius/Minor Axis:	1.0 in

## Standards

NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
ISO/IEC Compliance:	11801 ed 2.2 (2011) Class E
CPR Euroclass:	Eca
Data Category:	Category 6
ANSI Compliance:	S-116-732-2013 Category 6, ANSI/NEMA WC-66 Category 6
Telecommunications Standards:	ANSI/TIA-568-C.2 Category 6
IEEE Specification:	IEEE 802.3bt Type 1, Type 2, Type 3, Type 4
Other Standards:	C(UL)US CMP 90C OR (UL) CMP-LP (0.5A) OR CL3P-LP (0.5A)
Third Party Performance Verification:	Category 6

## Applicable Environmental and Other Programs

Environmental Space:	Plenum
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes

EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	Yes
EU CE Mark:	Yes
EU REACH SVHC Compliance (yyyy-mm-dd):	2017-07-10
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-13
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Aerial:	No
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Non-Halogenated:	No
Suitability - Oil Resistance:	No
Suitability - Outdoor:	No
Suitability - Sunlight Resistance:	No

## Flammability, LSOH, Toxicity Testing

C(UL) Flammability:	FT6
UL Flammability:	NFPA 262 Plenum (UL 910)
CSA Flammability:	FT6
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

## Part Number

Non-Plenum Number:	2412
--------------------	------

## Variants

Item #	Color	UPC	Length
2413 0101000	Black	612825061762	1,000 ft
2413 0102500	Black	612825061748	2,500 ft
2413 010A1000	Black	612825061755	1,000 ft
2413 010U1000	Black	612825131502	1,000 ft
2413 D151000	Blue	612825061601	1,000 ft
2413 D152500	Blue	612825061625	2,500 ft
2413 D15A1000	Blue	612825061618	1,000 ft
2413 D15U1000	Blue	612825061793	1,000 ft
2413 0081000	Gray	612825061717	1,000 ft
2413 008A1000	Gray	612825061724	1,000 ft
2413 008U1000	Gray	612825061809	1,000 ft
2413 0051000	Green	612825061663	1,000 ft
2413 0052500	Green	612825061670	2,500 ft
2413 005A1000	Green	612825061687	1,000 ft
2413 005U1000	Green	612825062226	1,000 ft
2413 0031000	Orange	612825061694	1,000 ft
2413 003A1000	Orange	612825061700	1,000 ft
2413 003U1000	Orange	612825062202	1,000 ft
2413 0035000	Orange	612825381068	
2413 0035000	Orange	612825381068	
2413 012A1000	Pink	612825061786	1,000 ft
2413 007A1000	Purple	612825061779	1,000 ft
2413 002A1000	Red	612825061731	1,000 ft
2413 0091000	White	612825061571	1,000 ft
2413 0092500	White	612825061595	2,500 ft
2413 009A1000	White	612825061588	1,000 ft
2413 009U1000	White	612825061816	1,000 ft

2413 0041000	Yellow	612825061632	1,000 ft
2413 0042500	Yellow	612825061656	2,500 ft
2413 004A1000	Yellow	612825061649	1,000 ft
2413 004U1000	Yellow	612825062219	1,000 ft

Patent: <https://www.belden.com/resources/patents>

## Product Notes

Notes: Values above 350 MHz are for Engineering Information Only. Print Includes Descending Footage/Meter Markings from Max. Put-Up Length to 0.

## History

Update and Revision: Revision Number: 0.352 Revision Date: 11-13-2019

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.