Detailed Specifications & Technical Data



AX102032 Faceplates and Panels - FiberExpress 1U Manager

□ (Me	Hanarat					For more Informatio please call	
						1-800-Belden1	
eneral Descrip	otion:						
iberExpress	Cable Ma	nagement Accessor	y, 1U, Bla	ck.			
sage (Overall)							
Suitable Applications:			FiberExpre	FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room			
Related Parts:			FiberExpre	FiberExpress Manager 1U Rack Mount Patch Panel			
hysical Charad	cteristics (Co	onnectivity)					
Capacity Max. Capacity:			Bracket op	ening of 1.6 in.)	X 2.7 in. (1U)		
Dimensions					(2.) (10)		
Dimensions:							
	Nidth (mm) Dept	· · ·					
	36.880 147.5	574					
Materials Materials:							
Description M	aterial						
Panel S	teel						
Color							
Color:			Black				
Included Parts							
Included Parts:			2 Screws (2 Screws (10-32); 1 Instruction Sheet; 1 Administration Label; 1 PFFA Label; 2 Velcro Straps.			
Packaging							
Packaging:			Individually	Individually packaged in a cardboard box.			
lechanical Cha	racteristics ((Connectivity)					
Storage Temperature Range:			-40°C To +	-40°C To +70°C			
Operating Temperature Range:			-10°C To +	-10°C To +60°C			
oplicable Spec	cifications an	nd Agency Compliance	(Overall)				
Suitability	and an and an	geney semphanoo	(3.5.6.4.1)				
Suitability - Ind	oor:		Yes				
ransmission C	haracteristic	cs (Connectivity)					
lotes (Overall)							
	per installation refe	er to Installation Guide PX103404	1 included with th	e product or visi	t our web site at http://www.belden.com		
Product Family							
	lors:						
out Ups and Co							
Put Ups and Co Item #	Putup	Ship Weight	Color	Notes	Item Desc		

Revision Number: 0 Revision Date: 03-30-2010

© 2016 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.