

7927A Multi-Conductor - Category 6 DataTuff® Twisted Pair Cable

For more Information
please call

1-800-Belden1



Description:

23 AWG Bonded-Pair solid bare copper conductors, polyolefin insulation, E-Spline center member, industrial grade sunlight- and oil-resistant PVC jacket, rip cord. Sequential marking at two foot intervals.

Usage (Overall)

Suitable Applications:

Industrial Ethernet Cable, Harsh Environments, 600 MHz Enhanced Category 6, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, RJ-45 Compatible

Physical Characteristics (Overall)

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 4 | 23 | Solid | BC - Bare Copper |

Total Number of Conductors:

8

Insulation

Insulation Material:

| Insulation Material |
|---------------------|
| PO - Polyolefin |

Outer Shield

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|---|
| Industrial Grade PVC - Polyvinyl Chloride |

Outer Jacket Ripcord:

Yes

Overall Cable

Overall Cabling Fillers:

E-Spline Center Member

Overall Cabling Color Code Chart:

| Number | Color |
|--------|-----------------------|
| 1 | White/Green & Green |
| 2 | White/Orange & Orange |
| 3 | White/Blue & Blue |
| 4 | White/Brown & Brown |

Overall Nominal Diameter:

6.375 x 8.611 mm

Mechanical Characteristics (Overall)

Installation Temperature Range:

-25°C To +75°C

Operating Temperature Range:

-40°C To +75°C

Bulk Cable Weight:

49.855 Kg/Km

7927A Multi-Conductor - Category 6 DataTuff® Twisted Pair Cable

Max. Recommended Pulling Tension: 200.169 N

Min. Bend Radius/Minor Axis: 6.350 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMR

AWM Specification: UL Style 444 (300 V 75°C)

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 10/13/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Other Specification: UL Verified to Category 6

Applicable Patents:

| Country | Patent |
|---------|---------|
| US | 5606151 |
| US | 5734126 |
| US | 6855889 |
| US | 7663061 |
| US | 7838773 |
| US | 7977575 |

Flame Test

UL Flame Test: UL1666 Riser

C(UL) Flame Test: FT4

Suitability

Sunlight Resistance: Yes

Oil Resistance: Yes

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

Capacitance (pF/m)

50.8555

Maximum Capacitance Unbalance (pF/100 m): 65.6

Nominal Velocity of Propagation:

VP (%)

67

Maximum Delay:

Delay (ns/100 m)

538 @ 100MHz

Max. Delay Skew:

Delay Skew (ns/100 m)

38

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)

METRIC MEASUREMENT VERSION

7927A Multi-Conductor - Category 6 DataTuff® Twisted Pair Cable

8.2

Max. Operating Voltage - UL:

Voltage
300 V RMS

Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)
3

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

| Freq. (MHz) | Max. Attenuation (dB/100 m) | Min. NEXT (dB) | Min. PSNEXT (dB) | Min. ACR (dB) | Min. PSACR (dB) | Min RL (dB) | Min. SRL (dB) |
|-------------|-----------------------------|----------------|------------------|---------------|-----------------|-------------|---------------|
| 1 | 1.9 | 82.3 | 80.3 | 80.5 | 78.5 | 20.0 | 27.0 |
| 4 | 3.6 | 73.3 | 71.3 | 69.7 | 67.7 | 23.0 | 27.0 |
| 8 | 5.1 | 68.8 | 66.8 | 63.7 | 61.7 | 24.5 | 27.0 |
| 10 | 5.7 | 67.3 | 65.3 | 61.6 | 59.6 | 25.0 | 27.0 |
| 16 | 7.2 | 64.3 | 62.3 | 57.0 | 55.0 | 25.0 | 27.0 |
| 20 | 8.1 | 62.8 | 60.8 | 54.7 | 52.7 | 25.0 | 27.0 |
| 25 | 9.1 | 61.3 | 59.3 | 52.3 | 50.3 | 25.0 | 27.0 |
| 31.25 | 10.2 | 59.9 | 57.9 | 49.7 | 47.7 | 25.0 | 27.0 |
| 62.5 | 14.7 | 55.4 | 53.4 | 40.7 | 38.7 | 25.0 | 27.0 |
| 100 | 18.9 | 52.3 | 50.3 | 33.4 | 31.4 | 25.0 | 27.0 |
| 155 | 23.9 | 49.5 | 47.5 | 25.5 | 23.5 | 22.8 | 24.7 |
| 200 | 27.5 | 47.8 | 45.8 | 20.3 | 18.3 | 21.7 | 23.4 |
| 250 | 31.2 | 46.3 | 44.3 | 15.2 | 13.2 | 20.5 | 22.2 |
| 300 | 34.5 | 43.2 | 41.2 | 10.6 | 8.6 | 20.2 | 21.2 |
| 310 | 35.2 | 42.9 | 40.9 | 9.8 | 7.8 | 20.1 | 21.1 |
| 350 | 37.7 | 42.2 | 40.2 | 6.5 | 4.5 | 19.8 | 20.4 |
| 400 | 40.6 | 41.3 | 39.3 | 2.6 | 0.6 | 19.5 | 19.7 |
| 450 | 43.5 | 40.5 | 38.5 | 2.1 | 0.10 | 18.9 | 19.1 |
| 460 | 44.0 | 40.4 | 38.4 | 0 | 0 | 18.8 | 19.0 |
| 500 | 46.2 | 39.8 | 37.8 | | | 18.4 | 18.5 |
| 550 | 48.8 | 39.2 | 37.2 | | | 18.0 | 18.0 |
| 600 | 51.4 | 38.6 | 36.6 | | | 17.6 | 17.6 |

Premise Cable Electrical Table 2:

| Freq. (MHz) | Input (Unfitted) Imp. (Ohms) | Fitted Impedance | Min. ELFEXT (dB) | Min. PSELFEXT (dB) |
|-------------|------------------------------|------------------|------------------|--------------------|
| 1 | 100 ± 12 | 100 ± 15 | 73.8 | 70.8 |
| 4 | 100 ± 12 | 100 ± 10.4 | 61.8 | 58.8 |
| 8 | 100 ± 12 | 100 ± 8 | 55.7 | 52.7 |
| 10 | 100 ± 12 | 100 ± 7.3 | 53.8 | 50.8 |
| 16 | 100 ± 12 | 100 ± 5.7 | 49.7 | 46.7 |
| 20 | 100 ± 12 | 100 ± 5 | 47.8 | 44.8 |
| 25 | 100 ± 15 | 100 ± 5 | 45.8 | 42.8 |
| 31.25 | 100 ± 15 | 100 ± 5 | 43.9 | 40.9 |
| 62.5 | 100 ± 15 | 100 ± 5 | 37.9 | 34.9 |
| 100 | 100 ± 15 | 100 ± 5 | 33.8 | 30.8 |
| 155 | 100 ± 15 | 100 ± 5 | 30.0 | 27.0 |
| 200 | 100 ± 15 | 100 ± 5 | 27.8 | 24.8 |
| 250 | 100 ± 20 | 100 ± 5 | 25.8 | 22.8 |
| 300 | 100 ± 20 | 100 ± 5 | 24.3 | 21.3 |
| 310 | 100 ± 20 | 100 ± 5 | 24.0 | 21.0 |
| 350 | 100 ± 22 | 100 ± 5 | 22.9 | 19.9 |
| 400 | 100 ± 22 | 100 ± 5 | 21.8 | 18.8 |
| 450 | 100 ± 22 | 100 ± 5 | 20.7 | 17.7 |
| 460 | 100 ± 22 | 100 ± 5 | 20.5 | 17.5 |
| 500 | 100 ± 22 | 100 ± 5 | 19.8 | 16.8 |
| 550 | 100 ± 22 | 100 ± 5 | 19.0 | 16.0 |
| 600 | 100 ± 22 | 100 ± 5 | 18.2 | 15.2 |

7927A Multi-Conductor - Category 6 DataTuff® Twisted Pair Cable

Notes (Overall)

Notes: Third party verified to TIA/EIA-568-B.2, Category 6. Operating temperature subject to length de-rating. Cable passes -40C Cold Bend per UL 1581.

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|---------------|--------|-------------|-------|-------|-----------------|
| 7927A 0101000 | 305 MT | 19.051 KG | BLACK | C | 4 PR #23 PP PVC |
| 7927A 0102000 | 610 MT | 38.102 KG | BLACK | C | 4 PR #23 PP PVC |

Notes:
C = CRATE REEL PUT-UP.

Revision Number: 6 Revision Date: 08-17-2011

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.