

ENSTO

PRODUCT SPECIFICATION

2/28/2019



6418677723773

KDN300

Mounting box

Code	KDN300
GTIN	6418677723773
ENumber	
Name	Mounting box EnstoNet Base + lid 3-pole
Description	Includes only base and lid. Couplers are to be ordered separately. Suitable coupler for box KDN300 is e.g. EnstoNet coupler NAC32.W. Suitable wiring connectors are KD160.03 or KD160.04.
Vendor	Ensto Finland Oy CE



Technical specification

Ratings

Rated voltage:	250 V
Degree of protection:	IP21
Rated current:	20 A
ETIM 7:	EC002600 Box/housing for surface mounting on the wall/ceiling

ETIM

ETIM

Cover model:	Suitable for snap-in connector (brand specific)
Mounting method:	Wall-/ceiling mounting
Material:	Plastic
Shape:	Rectangular
Number of inlets:	5
Equipped with:	None
Sealable:	false
Inlet from the rear:	true
Circuit integrity:	None

Rated insulation voltage Ui:	250 V
Length:	121 mm
Weatherproof:	false
For Ex-Zone dust:	None
Type of housing feed-through:	Preembossing
Tackable:	false
For Ex-zone gas:	None
Depth:	21 mm
Cover attachment:	Snapped on
Width:	95 mm
Explosion-tested version:	false
With screening:	false
Degree of protection (IP):	IP21
Castable:	false
Colour:	White
Casting compound included:	false
Surface protection:	Untreated

Packaging

Default package

Unit:	PCS
Size:	10
Length:	210 mm
Width:	210 mm
Height:	110 mm
Weight (brt):	0.716 kg
Volume:	4.851

Pallet package

Unit:	PCS
Size:	1250